

## INDUSTRIAL COMPONENT DATA

# 3SU1401-1BH00-3AA0 SIEMENS LED module with integrated LED, 24-240 V AC/DC, amber, spring-type terminal, for ..

Brand: SIEMENS | Manufacturer Part Number: 3SU1401-1BH00-3AA0



|                 |                                               |
|-----------------|-----------------------------------------------|
| Manufacturer    | SIEMENS                                       |
| MPN / Reference | 3SU1401-1BH00-3AA0                            |
| Catalog number  | 14011                                         |
| Category        | Lamp holder block for control circuit devices |
| Minimum order   | 1 Pcs                                         |
| Document ID     | EO-75B4142852                                 |
| Generated       | 2026-08-05                                    |

## Product Overview

LED module with integrated LED, 24-240 V AC/DC, amber, spring-type terminal, for front plate mounting  
LED MODULE C. INTEGRATED LED AC 24-240V, AMBER, SPRING TERMINALS, FOR FIXING ON FRONT PLATE.

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices

## Additional Product Information

## Technical data

LED module with integrated LED, 24-240 V AC/DC, amber, spring-type terminal, for front plate mounting

product brand name SIRIUS ACT

product designation LED module

product type designation 3SU1

## General technical data

product component

? diode Yes

? lamp transformer No

? light source Yes

? series resistor No

insulation voltage rated value 320 V

degree of pollution 3

type of voltage of the operating voltage AC/DC

? for actuation AC/DC  
surge voltage resistance rated value 4 kV  
consumed current maximum 20 mA  
protection class IP  
? of the enclosure IP40  
? of the terminal IP20  
shock resistance  
? according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms  
? for railway applications according to EN 61373 Category 1, Class B  
vibration resistance  
? according to IEC 60068-2-6 10 ... 500 Hz: 5g  
? for railway applications according to EN 61373 Category 1, Class B  
operating period typical 100 000 h  
reference code according to IEC 81346-2 P  
Substance Prohibitance (Date) 10/01/2014  
operating voltage  
? at AC  
- at 50 Hz rated value 24 ... 240 V  
- at 60 Hz rated value 24 ... 240 V  
? at DC rated value 24 ... 240 V  
relative positive tolerance of the operating voltage 20 %  
relative negative tolerance of the operating voltage 30 %  
Control circuit/ Control  
inrush current maximum 3 A  
Connections/ Terminals  
type of electrical connection spring-loaded terminals  
type of connectable conductor cross-sections  
? solid without core end processing 2x (0.25 ... 1.5 mm<sup>2</sup>)  
? finely stranded with co...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1401-1BH00-3AA0 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.