

INDUSTRIAL COMPONENT DATA

3SU1401-1BH20-3AA0 SIEMENS LED module with integrated LED, 24-240 V AC/DC, red, spring-type terminal, for fr..

Brand: SIEMENS | Manufacturer Part Number: 3SU1401-1BH20-3AA0



Manufacturer	SIEMENS
MPN / Reference	3SU1401-1BH20-3AA0
Catalog number	14011
Category	Lamp holder block for control circuit devices
Minimum order	1 Pcs
Document ID	EO-C75C902AD1
Generated	2026-08-03

Product Overview

LED module with integrated LED, 24-240 V AC/DC, red, spring-type terminal, for front plate mounting
LED C MODULE. INTEGRATED LED AC 24-240V, RED, SPRING TERMINALS, FOR FIXING ON FRONT PLATE.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices

Additional Product Information

Technical data

LED module with integrated LED, 24-240 V AC/DC, red, spring-type terminal, for front plate mounting

product brand name SIRIUS ACT

product designation LED module

product type designation 3SU1

General technical data

product component

? diode Yes

? lamp transformer No

? light source Yes

? series resistor No

insulation voltage rated value 320 V

degree of pollution 3

type of voltage of the operating voltage AC/DC

? for actuation AC/DC
surge voltage resistance rated value 4 kV
consumed current maximum 20 mA
protection class IP
? of the enclosure IP40
? of the terminal IP20
shock resistance
? according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms
? for railway applications according to EN 61373 Category 1, Class B
vibration resistance
? according to IEC 60068-2-6 10 ... 500 Hz: 5g
? for railway applications according to EN 61373 Category 1, Class B
operating period typical 100 000 h
reference code according to IEC 81346-2 P
Substance Prohibitance (Date) 10/01/2014
operating voltage
? at AC
- at 50 Hz rated value 24 ... 240 V
- at 60 Hz rated value 24 ... 240 V
? at DC rated value 24 ... 240 V
relative positive tolerance of the operating voltage 20 %
relative negative tolerance of the operating voltage 30 %
Control circuit/ Control
inrush current maximum 3 A
Connections/ Terminals
type of electrical connection spring-loaded terminals
type of connectable conductor cross-sections
? solid without core end processing 2x (0.25 ... 1.5 mm²)
? finely stranded with core...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1401-1BH20-3AA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.