

INDUSTRIAL COMPONENT DATA

3SU1401-2BF60-3AA0 SIEMENS LED module with integrated LED 230 V AC, white, spring-type terminal, for floor m..

Brand: SIEMENS | Manufacturer Part Number: 3SU1401-2BF60-3AA0



Manufacturer	SIEMENS
MPN / Reference	3SU1401-2BF60-3AA0
Catalog number	14012
Category	Lamp holder block for control circuit devices
Minimum order	1 Pcs
Document ID	EO-4B6EDEE4B6
Generated	2026-08-03

Product Overview

LED module with integrated LED 230 V AC, white, spring-type terminal, for floor mounting
LED MODULE WITH INTEGRATED 230V AC LED, WHITE, SPRING TERMINALS, FOR BASE FIXING.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices
--------------	---

Additional Product Information

Technical data

LED module with integrated LED 230 V AC, white, spring-type terminal, for floor mounting

product brand name SIRIUS ACT

product designation LED module

product type designation 3SU1

General technical data

product component

? diode Yes

? lamp transformer No

? light source Yes

? series resistor No

insulation voltage rated value 320 V

degree of pollution 3

type of voltage of the operating voltage AC

? for actuation AC
surge voltage resistance rated value 4 kV
consumed current maximum 20 mA
protection class IP
? of the enclosure IP40
? of the terminal IP20
shock resistance
? according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms
? for railway applications according to EN 61373 Category 1, Class B
vibration resistance
? according to IEC 60068-2-6 10 ... 500 Hz: 5g
? for railway applications according to EN 61373 Category 1, Class B
operating period typical 100 000 h
reference code according to IEC 81346-2 P
Substance Prohibitance (Date) 10/01/2014
operating voltage 1
? at AC
- at 50 Hz rated value 230 V
- at 60 Hz rated value 230 V
relative positive tolerance of the operating voltage 20 %
relative negative tolerance of the operating voltage 20 %
Control circuit/ Control
inrush current maximum 3 A
Connections/ Terminals
type of electrical connection spring-loaded terminals
type of connectable conductor cross-sections
? solid without core end processing 2x (0.25 ... 1.5 mm²)
? finely stranded with core end processing 2x (0.25 ... 0.75 mm²)
? finely stranded witho...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1401-2BF60-3AA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.