

**INDUSTRIAL COMPONENT DATA**

# 3SU1401-2EE60-6AA0 SIEMENS AS-Interface module, 2 safe inputs, 1 LED, white, spring-type terminal (push-in) ..

Brand: SIEMENS | Manufacturer Part Number: 3SU1401-2EE60-6AA0



|                 |                                             |
|-----------------|---------------------------------------------|
| Manufacturer    | SIEMENS                                     |
| MPN / Reference | 3SU1401-2EE60-6AA0                          |
| Catalog number  | 10000                                       |
| Category        | Accessories/spare parts for command devices |
| Minimum order   | 1 Pcs                                       |
| Document ID     | EO-4A5ECCFD68                               |
| Generated       | 2026-07-29                                  |

## Product Overview

AS-Interface module, 2 safe inputs, 1 LED, white, spring-type terminal (push-in) for floor mounting  
AS-interface module, 2 safe inputs, 1 LED, white, spring terminal (quick insert), for base fixing. Manufactured to order.  
Non-Cancelable Non-Returnable.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices**

## Additional Product Information

**Technical data**

AS-Interface module, 2 safe inputs, 1 LED, white, spring-type terminal (push-in) for floor mounting

product brand name SIRIUS ACT

product designation AS-Interface module

product type designation 3SU1

**General technical data**

product function 2F-DI / 1 LED

degree of pollution 3

type of voltage

? of the operating voltage DC

? of the input voltage DC

consumed current maximum 60 mA

protection class IP IP20

shock resistance for railway applications according to EN 61373 Category 1, Class B  
vibration resistance for railway applications according to EN 61373 Category 1, Class B  
reference code according to IEC 81346-2 K  
Substance Prohibitance (Date) 10/01/2014  
design of the slave type 2 F-DI + 1 LED  
AS-Interface slave profile S-7.B.0  
ID1 code 0...F  
number of AS-i slaves 1  
protocol is supported ASIsafe (Safety at work) protocol Yes  
operating voltage rated value 18 ... 31.6 V  
operating voltage 1 at DC rated value 30 V  
Communication/ Protocol  
protocol is supported AS-Interface protocol Yes  
Inputs/ Outputs  
number of digital inputs 0  
? safety-related 2  
number of digital outputs 1; For controlling the LED  
Connections/ Terminals  
type of electrical connection spring-loaded terminal (push-in)  
type of connectable conductor cross-sections  
? solid without core end processing 1x (0.14 ... 0.5 mm<sup>2</sup>)  
? finely stranded without core end processing 1x (0.2 ... 0.5 mm<sup>2</sup>)  
? at AWG cables 1x (26 ... 20)  
Lamp  
color of the light source white  
Product Function  
suitability for use safety-related c...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1401-2EE60-6AA0 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.