

INDUSTRIAL COMPONENT DATA

3SU1401-2EE60-6AA0 SIEMENS AS-Interface module, 2 safe inputs, 1 LED, white, spring-type terminal (push-in) ..

Brand: SIEMENS | Manufacturer Part Number: 3SU1401-2EE60-6AA0



Manufacturer	SIEMENS
MPN / Reference	3SU1401-2EE60-6AA0
Catalog number	10000
Category	Accessories/spare parts for command devices
Minimum order	1 Pcs
Document ID	EO-4A5ECCFD68
Generated	2026-08-01

Product Overview

AS-Interface module, 2 safe inputs, 1 LED, white, spring-type terminal (push-in) for floor mounting
AS-interface module, 2 safe inputs, 1 LED, white, spring terminal (quick insert), for base fixing. Manufactured to order.
Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices**

Additional Product Information

Technical data

AS-Interface module, 2 safe inputs, 1 LED, white, spring-type terminal (push-in) for floor mounting

product brand name SIRIUS ACT

product designation AS-Interface module

product type designation 3SU1

General technical data

product function 2F-DI / 1 LED

degree of pollution 3

type of voltage

? of the operating voltage DC

? of the input voltage DC

consumed current maximum 60 mA

protection class IP IP20

shock resistance for railway applications according to EN 61373 Category 1, Class B
vibration resistance for railway applications according to EN 61373 Category 1, Class B
reference code according to IEC 81346-2 K
Substance Prohibitance (Date) 10/01/2014
design of the slave type 2 F-DI + 1 LED
AS-Interface slave profile S-7.B.0
ID1 code 0...F
number of AS-i slaves 1
protocol is supported ASIsafe (Safety at work) protocol Yes
operating voltage rated value 18 ... 31.6 V
operating voltage 1 at DC rated value 30 V
Communication/ Protocol
protocol is supported AS-Interface protocol Yes
Inputs/ Outputs
number of digital inputs 0
? safety-related 2
number of digital outputs 1; For controlling the LED
Connections/ Terminals
type of electrical connection spring-loaded terminal (push-in)
type of connectable conductor cross-sections
? solid without core end processing 1x (0.14 ... 0.5 mm²)
? finely stranded without core end processing 1x (0.2 ... 0.5 mm²)
? at AWG cables 1x (26 ... 20)
Lamp
color of the light source white
Product Function
suitability for use safety-related c...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1401-2EE60-6AA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.