


INDUSTRIAL COMPONENT DATA

3SU1501-1AG40-1LA0 SIEMENS holder, 3-way, plastic, 1 NO+1 NC, 1 NO+1 NC, LED module, green, 6-24 V AC/DC, sc..

Brand: SIEMENS | Manufacturer Part Number: 3SU1501-1AG40-1LA0



Manufacturer	SIEMENS
MPN / Reference	3SU1501-1AG40-1LA0
Catalog number	15011
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-B6474CFAD4
Generated	2026-08-05

Product Overview

holder, 3-way, plastic, 1 NO+1 NC, 1 NO+1 NC, LED module, green, 6-24 V AC/DC, screw terminal
SUPPORT FOR 3 MODULES, PLASTIC, 1NA+1NC, 1NA+1NC, LED MODULE, GREEN, AC/DC 6-24V, SCREW
TERMINALS. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices**

Additional Product Information

Technical data

holder, 3-way, plastic, 1 NO+1 NC, 1 NO+1 NC, LED module, green, 6-24 V AC/DC, screw terminal

product brand name SIRIUS ACT

product designation Holders

product type designation 3SU1

manufacturer's article number

? of supplied contact module 3SU1400-1AA10-1FA0, 3SU1400-1AA10-1FA0

? of supplied contact module at position 1 3SU1400-1AA10-1FA0

? of supplied contact module at position 2 3SU1400-1AA10-1FA0

? of supplied LED module 3SU1401-1BG40-1AA0

? of the supplied holder 3SU1500-0AA10-0AA0

Actuator

design of the actuating element 3-way with module

number of contact modules 2
Holder
material of the holder Plastic
Display
number of LED modules 1
General technical data
product function positive opening Yes
product component
? diode Yes
? lamp transformer No
? light source Yes
? series resistor No
insulation voltage rated value 320 V
degree of pollution 3
surge voltage resistance rated value 4 kV
protection class IP of the terminal IP20, clamping screw tightened
shock resistance
? according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms
? for railway applications according to EN 61373 Category 1, Class B
vibration resistance
? according to IEC 60068-2-6 10 ... 500 Hz: 5g
? for railway applications according to EN 61373 Category 1, Class B
operating frequency maximum 3 600 1/h
mechanical service life (switching cycles) typical 10 000 000
thermal current 10 A
reference code according to IEC 81346-2 U
continuous current of the C characteristic MCB 10 A; for a short-...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1501-1AG40-1LA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.