


INDUSTRIAL COMPONENT DATA

3SU1501-1AG50-1CA0 SIEMENS holder, 3-way, plastic, 1 NC, LED module, blue, 6-24 V AC/DC, screw terminal

Brand: SIEMENS | Manufacturer Part Number: 3SU1501-1AG50-1CA0



Manufacturer	SIEMENS
MPN / Reference	3SU1501-1AG50-1CA0
Catalog number	15011
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-855416F5C7
Generated	2026-08-05

Product Overview

holder, 3-way, plastic, 1 NC, LED module, blue, 6-24 V AC/DC, screw terminal

SUPPORT FOR 3 MODULES, PLASTIC, 1NC, LED MODULE, BLUE, AC/DC 6-24V, SCREW TERMINALS. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices

Additional Product Information

Technical data

holder, 3-way, plastic, 1 NC, LED module, blue, 6-24 V AC/DC, screw terminal

product brand name SIRIUS ACT

product designation Holders

product type designation 3SU1

manufacturer's article number

? of supplied contact module 3SU1400-1AA10-1CA0

? of supplied contact module at position 1 3SU1400-1AA10-1CA0

? of supplied LED module 3SU1401-1BG50-1AA0

? of the supplied holder 3SU1500-0AA10-0AA0

Actuator

design of the actuating element 3-way with module

number of contact modules 1

Holder

material of the holder Plastic

Display

number of LED modules 1

General technical data

product function positive opening Yes

product component

? diode Yes

? lamp transformer No

? light source Yes

? series resistor No

insulation voltage rated value 320 V

degree of pollution 3

surge voltage resistance rated value 4 kV

protection class IP of the terminal IP20

shock resistance

? according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms

? for railway applications according to EN 61373 Category 1, Class B

vibration resistance

? according to IEC 60068-2-6 10 ... 500 Hz: 5g

? for railway applications according to EN 61373 Category 1, Class B

operating frequency maximum 3 600 1/h

mechanical service life (switching cycles) typical 10 000 000

thermal current 10 A

reference code according to IEC 81346-2 U

continuous current of the C characteristic MCB 10 A; for a short-circuit current smaller than 400 A

continuous current of the quick DIAZED fuse link 10 A

continuous current of the DIAZED fus...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1501-1AG50-1CA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.