

INDUSTRIAL COMPONENT DATA

3SU1550-0BA10-0AA0 SIEMENS Holder for 4 modules, metal, for selector switch with 4 switch positions and for ..

Brand: SIEMENS | Manufacturer Part Number: 3SU1550-0BA10-0AA0



Manufacturer	SIEMENS
MPN / Reference	3SU1550-0BA10-0AA0
Catalog number	15500
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-97B7BCFD55
Generated	2026-08-01

Product Overview

holder, 4-way, metal, for selector switch with 4 switch positions and for coordinate switch

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices**

Additional Product Information

Technical data

holder, 4-way, metal, for selector switch with 4 switch positions and for coordinate switch

product brand name SIRIUS ACT

product designation Holders

product type designation 3SU1

manufacturer's article number

? of the supplied holder 3SU1550-0AA10-0AA0

Actuator

design of the actuating element 4-way without module

number of contact modules 0

Holder

material of the holder Metal

Display

number of LED modules 0

General technical data

product function positive opening No
product component
? diode No
? lamp transformer No
? light source No
? series resistor No
insulation voltage rated value 500 V
degree of pollution 3
surge voltage resistance rated value 6 kV
shock resistance
? according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms
? for railway applications according to EN 61373 Category 1, Class B
vibration resistance
? according to IEC 60068-2-6 10 ... 500 Hz: 5g
? for railway applications according to EN 61373 Category 1, Class B
reference code according to IEC 81346-2 U
Substance Prohibitance (Date) 10/01/2014
Auxiliary circuit
number of NC contacts for auxiliary contacts 0
number of NO contacts for auxiliary contacts 0
Connections/ Terminals
tightening torque of the screws in the bracket 1 ... 1.2 N·m
tightening torque
? for grounding 0.8 ... 1 N·m
Ambient conditions
ambient temperature
? during operation -25 ... +70 °C
? during storage -40 ... +80 °C
environmental category during operation according to IEC 60721 3M6, 3S2, 3B2, 3C3, 3K6 (with relative a...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1550-0BA10-0AA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.