

INDUSTRIAL COMPONENT DATA

3SU1801-1AA00-1AA1 SIEMENS Enclosure for 4 position knob, coordinate, ID key-operated switches and sensor sw..

Brand: SIEMENS | Manufacturer Part Number: 3SU1801-1AA00-1AA1



Manufacturer	SIEMENS
MPN / Reference	3SU1801-1AA00-1AA1
Catalog number	18011
Category	Enclosure for control circuit devices
Minimum order	1 Pcs
Document ID	EO-F4EB7EAAF1
Generated	2026-08-02

Product Overview

Enclosure for 4 position knob, coordinate, ID key-operated switches and sensor switches, 22 mm, round, Enclosure material plastic, enclosure top part gray, 1 control point plastic, without equipment, only for front plate mounting

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices
--------------	---

Additional Product Information

Technical data

Enclosure for 4 position knob, coordinate, ID key-operated switches and sensor switches, 22 mm, round, Enclosure material plastic, enclosure top part gray, 1 control point plastic, without equipment, only for front plate mounting

product brand name SIRIUS ACT

product designation Enclosures

product type designation 3SU1

Enclosure

design of the housing Command point in center

shape of the enclosure front Square

material of the enclosure plastic

number of command points 1

product component protective collar No

color of the enclosure top part grey

fastening method of the enclosure Vertical / horizontal

General technical data

protection class IP IP66, IP67, IP69(IP69K)

degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13

shock resistance for railway applications according to EN 61373 Category 1, Class B

vibration resistance for railway applications according to EN 61373 Category 1, Class B

Substance Prohibitance (Date) 10/01/2014

cable entry type Without

Connections/ Terminals

type of electrical connection on enclosure Cable routing above and below, both 1 x M20

tightening torque of fixing screws in the enclosure cover 1.5 ... 1.7 N·m

Ambient conditions

ambient temperature

? during operation -25 ... +70 °C

? during storage -40 ... +80 °C

environmental category during operation according to IEC 60721 3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 ... 95%, no condensation in operation permitted for all devices behind front panel)

Installation/ mount...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1801-1AA00-1AA1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.