

INDUSTRIAL COMPONENT DATA

3SU1803-3AA00-0AA1 SIEMENS Two-hand operation console for command devices, 22 mm, round, Enclosure material ..

Brand: SIEMENS | Manufacturer Part Number: 3SU1803-3AA00-0AA1



Manufacturer	SIEMENS
MPN / Reference	3SU1803-3AA00-0AA1
Catalog number	18033
Category	Two-hand control device
Minimum order	1 Pcs
Document ID	EO-FF2F66DA42
Generated	2026-08-01

Product Overview

two-hand operation console for command devices, 22 mm, round, enclosure material plastic, enclosure top part gray, 3 holes for command points, 8 additional preset breaking points for 22 mm command devices, without equipment, with cable cut-outs for metric screw connections

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices**

Additional Product Information

Technical data

two-hand operation console for command devices, 22 mm, round, enclosure material plastic, enclosure top part gray, 3 holes for command points, 8 additional preset breaking points for 22 mm command devices, without equipment, with cable cut-outs for metric screw connections

product brand name SIRIUS ACT

product designation Two-hand operation console

product type designation 3SU1

Enclosure

design of the housing Two-hand operating console without standard equipment

material of the enclosure plastic

number of command points 3

color of the enclosure top part grey

delivery state

? as a kit No
? pre-wired on strip terminal No
fastening method of the enclosure Horizontal
Actuator
design of the actuating element Unequipped
principle of operation of the actuating element without
product feature
? lockout No
? staggered switching No
number of contact modules 0
General technical data
product function
? positive opening No
? EMERGENCY OFF function No
? EMERGENCY STOP function No
product component stand/pedestal No
protection class IP IP66
degree of protection NEMA rating 1, 4X, 12K, indoor use only, 13
shock resistance according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms
vibration resistance according to IEC 60068-2-6 10 ... 500 Hz: 5g
reference code according to IEC 81346-2 U
Substance Prohibitance (Date) 10/01/2014
Auxiliary circuit
number of NC contacts for auxiliary contacts 0
number of NO contacts for auxiliary contacts 0
Connections/ Terminals
type of electri...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1803-3AA00-0AA1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.