

INDUSTRIAL COMPONENT DATA

3SU1851-0AA00-0AB2 SIEMENS Enclosure for command devices, 22 mm, round, Enclosure material metal, Enclosure ..

Brand: SIEMENS | Manufacturer Part Number: 3SU1851-0AA00-0AB2



Manufacturer	SIEMENS
MPN / Reference	3SU1851-0AA00-0AB2
Catalog number	18510
Category	Enclosure for control circuit devices
Minimum order	1 Pcs
Document ID	EO-9362750BE9
Generated	2026-08-05

Product Overview

Enclosure for command devices, 22 mm, round, Enclosure material metal, Enclosure top part yellow, 1 control point metal, Recess for label, without equipment
CONTROL BOX, 22MM, ROUND, MATAL BOX, YELLOW TOP, 1 METAL CONTROL POINT, RECESS FOR INSERTS, UNEQUIPPED

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices**

Additional Product Information

Technical data

Enclosure for command devices, 22 mm, round, Enclosure material metal, Enclosure top part yellow, 1 control point metal, Recess for label, without equipment
product brand name SIRIUS ACT
product designation Enclosures
product type designation 3SU1
Enclosure
design of the housing with recess for label
shape of the enclosure front Square
material of the enclosure metal
number of command points 1
product component protective collar No

color of the enclosure top part yellow

fastening method of the enclosure Vertical / horizontal

General technical data

protection class IP IP66, IP67, IP69(IP69K)

degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13

shock resistance for railway applications according to EN 61373 Category 1, Class B

vibration resistance for railway applications according to EN 61373 Category 1, Class B

Substance Prohibitance (Date) 10/01/2014

cable entry type Without

Connections/ Terminals

type of electrical connection on enclosure Cable routing above and below, both 1 x M20

tightening torque of fixing screws in the enclosure cover 1.5 ... 1.7 N·m

Ambient conditions

ambient temperature

? during operation -25 ... +70 °C

? during storage -40 ... +80 °C

environmental category during operation according to IEC 60721 3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 ... 95%, no condensation in operation permitted for all devices behind front panel)

Installation/ mounting/ dimensions

fastening method of modules and accessories Floor mounting....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1851-0AA00-0AB2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.