

INDUSTRIAL COMPONENT DATA

3TH2022-0BW4 SIEMENS Contactor relay, 22E, EN 50011, 2 NO + 2 NC, Screw terminal DC operation 48 V DC !!! Ph..

Brand: SIEMENS | Manufacturer Part Number: 3TH2022-0BW4



Manufacturer	SIEMENS
MPN / Reference	3TH2022-0BW4
Catalog number	20220
Category	Contactor relay
Minimum order	1 Pcs
Document ID	EO-A1A172AA8E
Generated	2026-08-05

Product Overview

Contactor relay, 22E, EN 50011, 2 NO + 2 NC, Screw terminal DC operation 48 V DC !!! Phased-out product !!! Successor is SIRIUS 3RH21

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Contactor relays

Additional Product Information

ETIM: EC000196 - Contactor relay

Value Unit

Interface (EF000594) -

With LED indication (EF005950) -

Mounting method (EF000003) -

Manual operation possible (EF005881) -

Rated control supply voltage U_s at DC (EF003980) ['-', '48'] V

Voltage type for actuating (EF008242) DC

Rated operation current I_e , 400 V (EF001378) 3 A

Connection type auxiliary circuit (EF006820) Screw connection

Number of auxiliary contacts as normally closed contact (EF001377) 2

Number of auxiliary contacts as normally open contact (EF001376) 2

Number of auxiliary contacts as normally closed contact, delayed switching (EF007281) 0

Number of auxiliary contacts as normally open contact, leading (EF007282) 0

Number of auxiliary contacts as change-over contact (EF003531) 0

Rated control supply voltage Us at AC 50HZ (EF003978) - V

Rated control supply voltage Us at AC 60HZ (EF003979) - V

Contactor relay, 22E, EN 50011, 2 NO + 2 NC, Screw terminal DC operation 48 V DC !!! Phased-out product !!! Successor is SIRIUS 3RH21

product designation Auxiliary contactor

product type designation 3TH2

Size of contactor 0

protection class IP on the front IP20

reference code acc. to DIN EN 81346-2 K

? ambient temperature during operation -25 ... +55 °C

Type of voltage of the control supply voltage DC

control supply voltage at DC

? rated value 48 V

? number of NC contacts for auxiliary contacts 2

? Number of NC contacts for auxiliary contacts delayed switching 0

? Number of NC contacts for auxiliary contacts lagging switching 0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3TH2022-0BW4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.