

INDUSTRIAL COMPONENT DATA

3TH2040-3JB4 SIEMENS Contactor relay, 40E, EN 50011, 4 NO + 0 NC flat connector terminal Snap-on mounting, w..

Brand: SIEMENS | Manufacturer Part Number: 3TH2040-3JB4



Manufacturer	SIEMENS
MPN / Reference	3TH2040-3JB4
Catalog number	20403
Category	Contacteur relay
Minimum order	1 Pcs
Document ID	EO-D5972E534E
Generated	2026-08-04

Product Overview

Contacteur relay, 40E, EN 50011, 4 NO + 0 NC flat connector terminal Snap-on mounting, with diode 24 V DC DC operation
!!! Phased-out product !!! Successor is SIRIUS 3RH21

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > CONTROL AND CONTACTORS > Contacteur relays
--------------	--

Additional Product Information

ETIM: EC000196 - Contacteur relay

Value Unit

Mounting method (EF000003) -

With LED indication (EF005950) -

Interface (EF000594) -

Manual operation possible (EF005881) -

Rated control supply voltage U_s at DC (EF003980) ['-', '24'] V

Voltage type for actuating (EF008242) DC

Rated operation current I_e , 400 V (EF001378) 3 A

Connection type auxiliary circuit (EF006820) Other

Number of auxiliary contacts as normally closed contact (EF001377) 0

Number of auxiliary contacts as normally open contact (EF001376) 4

Number of auxiliary contacts as normally closed contact, delayed switching (EF007281) 0

Number of auxiliary contacts as normally open contact, leading (EF007282) 0

Number of auxiliary contacts as change-over contact (EF003531) 0

Rated control supply voltage Us at AC 50HZ (EF003978) - V

Rated control supply voltage Us at AC 60HZ (EF003979) - V

Contactor relay, 40E, EN 50011, 4 NO + 0 NC flat connector terminal Snap-on mounting, with diode 24 V DC DC operation

!!! Phased-out product !!! Successor is SIRIUS 3RH21

Product designation Auxiliary contactor

Product type designation 3TH2

Size of contactor 0

protection class IP on the front IP00

Reference code acc. to DIN EN 81346-2 K

Ambient temperature

? during operation -25 ... +55 °C

Type of voltage of the control supply voltage DC

Control supply voltage at DC

? rated value 24 V

Design of the surge suppressor with diode

Number of NC contacts for auxiliary contacts 0

? delayed switching 0

? lagging switching 0

? make-before-break swi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3TH2040-3JB4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.