

INDUSTRIAL COMPONENT DATA

3TH4262-5KB4 SIEMENS Contactor relay, 62E, DIN EN 50011, 6 NO + 2 NC flat connector terminal DC operation 24..

Brand: SIEMENS | Manufacturer Part Number: 3TH4262-5KB4



Manufacturer	SIEMENS
MPN / Reference	3TH4262-5KB4
Catalog number	42625
Category	Contactor relay
Minimum order	1 Pcs
Document ID	EO-FC9368943E
Generated	2026-08-04

Product Overview

Contactor relay, 62E, DIN EN 50011, 6 NO + 2 NC flat connector terminal DC operation 24 V DC integrated varistor
SIRIUS Auxiliary contactor OF 2 PLANES, DC 24V, TAM. 0, integrated 6NA+2NC varistor

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Contactor relays**

Additional Product Information

Technical data

Contactor relay, 62E, DIN EN 50011, 6 NO + 2 NC flat connector terminal DC operation 24 V DC integrated varistor

product designation Auxiliary contactor

product type designation 3TH4

size of contactor 0

reference code according to IEC 81346-2 K

Substance Prohibitance (Date) 03/01/2017

ambient temperature during operation -25 ... +55 °C

type of voltage of the control supply voltage DC

control supply voltage at DC

? rated value 24 V

design of the surge suppressor with varistor

number of NC contacts for auxiliary contacts 2

? delayed switching 0

? lagging switching 0
? make-before-break switching 0
number of NO contacts for auxiliary contacts 6
? delayed switching 0
? leading contact 0
? make-before-break switching 0
number of CO contacts for auxiliary contacts 0
identification number and letter for switching elements 62 E
operational current at AC-15
? at 230 V rated value 10 A
? at 400 V rated value 6 A
fastening method screw and snap-on mounting onto 35 mm DIN rail according to DIN EN 50022
height 78 mm
width 45 mm
depth 135 mm
type of electrical connection for auxiliary and control circuit screw-type terminals
Safety related data
B10 value with high demand rate according to SN 31920 1 000 000; With $0.3 \times I_e$
T1 value for proof test interval or service life according to IEC 61508 20 a
protection class IP on the front according to IEC 60529 IP00
Certificates/ approvals
Downloads and manuals
General Product Approval Functional Safety/Safety of Machinery Declarati...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3TH4262-5KB4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.