

**INDUSTRIAL COMPONENT DATA**

# 3TH4382-0BM4 SIEMENS Contactor relay, 82E, EN 50011, 8 NO + 2 NC, screw terminal, DC operation, 220 V DC

Brand: SIEMENS | Manufacturer Part Number: 3TH4382-0BM4



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | SIEMENS         |
| MPN / Reference | 3TH4382-0BM4    |
| Catalog number  | 43820           |
| Category        | Contactor relay |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-BE2465A7B9   |
| Generated       | 2026-08-05      |

## Product Overview

Contactor relay, 82E, EN 50011, 8 NO + 2 NC, screw terminal, DC operation, 220 V DC  
SIRIUS Auxiliary Contactor IL.82E DIN EN 50 011 8NA+2NC, screw connection ACCIONAM. BY DIRECT CURRENT MAGNETIC SYSTEM DC DC 220V.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Contactor relays**

## Additional Product Information

**Technical data**

Contactor relay, 82E, EN 50011, 8 NO + 2 NC, screw terminal, DC operation, 220 V DC

product designation Auxiliary contactor

product type designation 3TH4

size of contactor 0

reference code according to IEC 81346-2 K

Substance Prohibitance (Date) 03/01/2017

ambient temperature during operation -25 ... +55 °C

type of voltage of the control supply voltage DC

control supply voltage at DC

? rated value 220 V

number of NC contacts for auxiliary contacts 2

? delayed switching 0

? lagging switching 0  
? make-before-break switching 0  
number of NO contacts for auxiliary contacts 8  
? delayed switching 0  
? leading contact 0  
? make-before-break switching 0  
number of CO contacts for auxiliary contacts 0  
identification number and letter for switching elements 82 E  
operational current at AC-15  
? at 230 V rated value 10 A  
? at 400 V rated value 6 A  
fastening method screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 50022  
height 78 mm  
width 55 mm  
depth 135 mm  
type of electrical connection for auxiliary and control circuit screw-type terminals  
Safety related data  
B10 value with high demand rate according to SN 31920 1 000 000; With 0.3 x I<sub>e</sub>  
Downloads and manuals  
protection class IP on the front according to IEC 60529 IP00  
Further information  
Information- and Downloadcenter (Catalogs, Brochures,...)<https://www.siemens.com/ic10>  
Industry Mall (Online ordering system)<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3TH4382-0BM4>  
Cax online....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3TH4382-0BM4 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.