

## INDUSTRIAL COMPONENT DATA

# 3TK1042-0AU0 SIEMENS Contactor, AC-1, 4-pin, 200 A, main contacts 4 NO, Auxiliary contacts 2 NO + 2 NC, AC o..

Brand: SIEMENS | Manufacturer Part Number: 3TK1042-0AU0



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | SIEMENS                       |
| MPN / Reference | 3TK1042-0AU0                  |
| Catalog number  | 10420                         |
| Category        | Power contactor, AC switching |
| Minimum order   | 1 Pcs                         |
| Document ID     | EO-4F971A9C08                 |
| Generated       | 2026-08-04                    |

## Product Overview

Contactor, AC-1, 4-pin, 200 A, main contacts 4 NO, Auxiliary contacts 2 NO + 2 NC, AC operation 230...240 V AC 50 Hz !!!  
Phased-out product !!! Successor is SIRIUS 3RT Preferred successor type is 3RT1355-6AP36

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors

## Additional Product Information

ETIM: EC000066 - Power contactor, AC switching  
Value Unit  
Rated operation power NEMA (EF011960) - kW  
Rated operation current Ie at AC-1, 400 V (EF001393) - A  
Rated control supply voltage Us at AC 50HZ (EF003978) ['230.0', '240.0'] V  
Rated control supply voltage Us at DC (EF003980) ['- ', '- '] V  
Voltage type for actuating (EF008242) AC  
Rated operation current Ie at AC-3, 400 V (EF001392) 120 A  
Rated operation power at AC-3, 400 V (EF001364) 55.0 kW  
Rated operation current Ie at AC-4, 400 V (EF008495) - A  
Modular version (EF001126) true  
Number of auxiliary contacts as normally open contact (EF001376) 2  
Number of auxiliary contacts as normally closed contact (EF001377) 2  
Type of electrical connection of main circuit (EF006819) Screw connection

Number of normally closed contacts as main contact (EF001375) 0  
Number of main contacts as normally open contact (EF001374) 4  
Rated operation power at AC-4, 400 V (EF008496) - kW  
Rated control supply voltage Us at AC 60HZ (EF003979) - V  
Contactor, AC-1, 4-pin, 200 A, main contacts 4 NO, Auxiliary contacts 2 NO + 2 NC, AC operation 230...240 V AC 50 Hz !!!  
Phased-out product !!! Successor is SIRIUS 3RT Preferred successor type is 3RT1355-6AP36  
protection class IP on the front IP00  
Reference code acc. to DIN EN 81346-2 Q  
Ambient temperature  
? during operation -25 ... +55 °C  
Number of poles for main current circuit 4  
Number of NO contacts for main contacts 4  
Number of NC contacts for main contacts 0  
Operating current  
? at AC-1 at 400 V  
- at a...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3TK1042-0AU0 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.