

INDUSTRIAL COMPONENT DATA

3TK1910-3A SIEMENS 1st auxiliary switch block for lateral mounting to contactors left or right 1 NO + 1 NC

Brand: SIEMENS | Manufacturer Part Number: 3TK1910-3A



Manufacturer	SIEMENS
MPN / Reference	3TK1910-3A
Catalog number	19103
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-A1C147FFD7
Generated	2026-08-05

Product Overview

1st auxiliary switch block for lateral mounting to contactors left or right 1 NO + 1 NC

1. auxiliary contact block for side mounting in SIRIUS Contactor, left or right, 1NA+1NC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors**

Additional Product Information

Technical data

1st auxiliary switch block for lateral mounting to contactors left or right 1 NO + 1 NC

product brand name SIRIUS

product designation auxiliary switch

suitability for use Contactor relay and power contactor

General technical data

insulation voltage with degree of pollution 3 at AC rated value 690 V

surge voltage resistance rated value 6 kV

protection class IP on the front IP20

mechanical service life (operating cycles) typical 10 000 000

Substance Prohibitance (Date) 07/01/2006

number of NC contacts for auxiliary contacts

? instantaneous contact 1

? lagging switching 0

number of NO contacts for auxiliary contacts
? instantaneous contact 1
? leading contact 0
number of CO contacts of auxiliary contacts instantaneous contact 0
operational current at AC-15 at 690 V rated value 2.3 A
operational current of auxiliary contacts at AC-12
? at 24 V 10 A
? at 230 V 10 A
operational current of auxiliary contacts at AC-14
? at 125 V 10 A
operational current of auxiliary contacts at AC-12 maximum 10 A
operational current of auxiliary contacts at AC-15
? at 24 V 10 A
? at 230 V 5.6 A
? at 400 V 3.6 A
operational current of auxiliary contacts at DC-13
? at 24 V 10 A
? at 48 V 5 A
? at 60 V 5 A
? at 110 V 1.14 A
? at 125 V 0.98 A
? at 220 V 0.48 A
Ambient conditions
ambient temperature
? during operation -25 ... +55 °C
? during storage -55 ... +80 °C
Safety related data
product function
? positively driven operation according to IEC 60947-5-1 Yes
Installation/ mounting/ dimen...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3TK1910-3A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.