

INDUSTRIAL COMPONENT DATA

3TK2022-6AC2 SIEMENS Miniature contactor, soldering pin connection, 2 NO + 2 NC Screw mounting (diagonal) 24..

Brand: SIEMENS | Manufacturer Part Number: 3TK2022-6AC2



Manufacturer	SIEMENS
MPN / Reference	3TK2022-6AC2
Catalog number	20226
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-F55D87FAB4
Generated	2026-08-05

Product Overview

Miniature contactor, soldering pin connection, 2 NO + 2 NC Screw mounting (diagonal) 24 V AC 50/60 Hz AC operation !!!
Phased-out product !!! Successor is SIRIUS 3RT23/25

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors

Additional Product Information

ETIM: EC000066 - Power contactor, AC switching
Value Unit
Rated operation power NEMA (EF011960) - kW
Rated operation current I_e at AC-1, 400 V (EF001393) - A
Rated control supply voltage U_s at DC (EF003980) ['- ', '-'] V
Voltage type for actuating (EF008242) AC
Rated operation current I_e at AC-3, 400 V (EF001392) 9 A
Rated operation power at AC-3, 400 V (EF001364) 4.0 kW
Rated operation current I_e at AC-4, 400 V (EF008495) - A
Modular version (EF001126) true
Number of auxiliary contacts as normally open contact (EF001376) 0
Number of auxiliary contacts as normally closed contact (EF001377) 0
Type of electrical connection of main circuit (EF006819) Other
Number of normally closed contacts as main contact (EF001375) 2

Number of main contacts as normally open contact (EF001374) 2

Rated operation power at AC-4, 400 V (EF008496) - kW

Rated control supply voltage Us at AC 50HZ (EF003978) - V

Rated control supply voltage Us at AC 60HZ (EF003979) - V

Miniature contactor, soldering pin connection, 2 NO + 2 NC Screw mounting (diagonal) 24 V AC 50/60 Hz AC operation !!!

Phased-out product !!! Successor is SIRIUS 3RT23/25

product designation Miniature contactor

product type designation 3TK20

Size of contactor 0

protection class IP on the front IP00

reference code acc. to DIN EN 81346-2 Q

? ambient temperature during operation -25 ... +55 °C

number of poles for main current circuit 4

Number of NO contacts for main contacts 2

Number of NC contacts for main contacts 2

? Operating current at...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3TK2022-6AC2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.