

## INDUSTRIAL COMPONENT DATA

# 3TK2022-7AL2 SIEMENS Miniature contactor, Flat connector terminal 2 NO + 2 NC Screw mounting (diagonal) 230/..

Brand: SIEMENS | Manufacturer Part Number: 3TK2022-7AL2



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | SIEMENS                       |
| MPN / Reference | 3TK2022-7AL2                  |
| Catalog number  | 20227                         |
| Category        | Power contactor, AC switching |
| Minimum order   | 1 Pcs                         |
| Document ID     | EO-8374951521                 |
| Generated       | 2026-08-03                    |

## Product Overview

Miniature contactor, Flat connector terminal 2 NO + 2 NC Screw mounting (diagonal) 230/220 V AC 50/60 Hz AC operation  
!!! Phased-out product !!! Successor is SIRIUS 3RT23/25

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors

## Additional Product Information

ETIM: EC000066 - Power contactor, AC switching

Value Unit

Rated operation power NEMA (EF011960) - kW

Rated operation current I<sub>e</sub> at AC-1, 400 V (EF001393) - A

Rated control supply voltage U<sub>s</sub> at DC (EF003980) ['-', '-'] V

Voltage type for actuating (EF008242) AC

Rated operation current I<sub>e</sub> at AC-3, 400 V (EF001392) 9 A

Rated operation power at AC-3, 400 V (EF001364) 4.0 kW

Rated operation current I<sub>e</sub> at AC-4, 400 V (EF008495) - A

Modular version (EF001126) true

Number of auxiliary contacts as normally open contact (EF001376) 0

Number of auxiliary contacts as normally closed contact (EF001377) 0

Type of electrical connection of main circuit (EF006819) Flat plug-in connection

Number of normally closed contacts as main contact (EF001375) 2

Number of main contacts as normally open contact (EF001374) 2

Rated operation power at AC-4, 400 V (EF008496) - kW

Rated control supply voltage Us at AC 50HZ (EF003978) - V

Rated control supply voltage Us at AC 60HZ (EF003979) - V

Miniature contactor, Flat connector terminal 2 NO + 2 NC Screw mounting (diagonal) 230/220 V AC 50/60 Hz AC operation

!!! Phased-out product !!! Successor is SIRIUS 3RT23/25

product designation Miniature contactor

product type designation 3TK20

Size of contactor 0

protection class IP on the front IP00

reference code acc. to DIN EN 81346-2 Q

? ambient temperature during operation -25 ... +55 °C

number of poles for main current circuit 4

Number of NO contacts for main contacts 2

Number of NC contacts for main contacts 2

?...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3TK2022-7AL2 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.