

INDUSTRIAL COMPONENT DATA

3TX4413-0B SIEMENS Auxiliary switch block, with flat connector terminal for contactor relays EN 50011, Ident..

Brand: SIEMENS | Manufacturer Part Number: 3TX4413-0B



Manufacturer	SIEMENS
MPN / Reference	3TX4413-0B
Catalog number	44130
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-1A64BD533F
Generated	2026-08-05

Product Overview

Auxiliary switch block, with flat connector terminal for contactor relays EN 50011, Ident. no. 53E, 1 NO + 3 NC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Contactor relays**

Additional Product Information

ETIM: EC000041 - Auxiliary contact block

Value Unit

Type of electric connection (EF003961) -

Number of contacts as normally closed contact (EF008255) -

Number of contacts as change-over contact (EF008257) -

Mounting method (EF000003) -

Number of contacts as normally open contact (EF008256) -

Model (EF000010) -

Rated operation current Ie at AC-15, 230 V (EF001385) - A

Number of fault-signal switches (EF007613) 0

Lamp holder (EF000048) None

Auxiliary switch block, with flat connector terminal for contactor relays EN 50011, Ident. no. 53E, 1 NO + 3 NC

General technical data

Suitability for use Contactor relay and power contactor

Protection class IP on the front IP20

Ambient temperature

? during storage -55 ... +80 °C

? during operation -25 ... +55 °C

Mechanical service life (switching cycles) typical 10 000 000

Insulation voltage with degree of pollution 3 at AC rated value 690 V

Surge voltage resistance rated value 6 kV

Auxiliary circuit

Number of NC contacts for auxiliary contacts

? instantaneous contact 3

? lagging switching 0

Number of NO contacts for auxiliary contacts

? instantaneous contact 1

? leading contact 0

Operating current of auxiliary contacts at AC-12

? at 24 V 10 A

? at 230 V 10 A

? maximum 10 A

Operating current

? of auxiliary contacts

- at AC-14

- at 125 V 10 A

- at AC-15

- at 24 V 10 A

- at 230 V 5.6 A

- at 400 V 3.6 A

? at AC-15 at 690 V rated value 2.3 A

Operating current

? of auxiliary contacts at DC-12

- at 24 V 4 A

- at 110 V 1.1 A

- at 220 V 0.5 A

Oper...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3TX4413-0B with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.