

**INDUSTRIAL COMPONENT DATA**

# 3UF7013-1AB00-0 SIEMENS Basic unit SIMOCODE pro V EIP, EtherNet/IP, medium redundancy DLR, Web server, trans..

Brand: SIEMENS | Manufacturer Part Number: 3UF7013-1AB00-0



|                 |                         |
|-----------------|-------------------------|
| Manufacturer    | SIEMENS                 |
| MPN / Reference | 3UF7013-1AB00-0         |
| Catalog number  | 70131                   |
| Category        | Motor management device |
| Minimum order   | 1 Pcs                   |
| Document ID     | EO-93611DF38F           |
| Generated       | 2026-08-01              |

## Product Overview

Basic unit SIMOCODE pro V EIP, EtherNet/IP, medium redundancy DLR, Web server, transmission rate 100 Mbps, 2 x bus connection via RJ45, 4I/3O freely parameterizable, Us: 24 V DC, input for thermistor connection Monostable relay outputs, expandable by extension modules

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > AS-Interface switchgear, SIMOCODE**

## Additional Product Information

**Technical data**

Basic unit SIMOCODE pro V EIP, EtherNet/IP, medium redundancy DLR, Web server, transmission rate 100 Mbps, 2 x bus connection via RJ45, 4I/3O freely parameterizable, Us: 24 V DC, input for thermistor connection Monostable relay outputs, expandable by extension modules

product brand name SIRIUS

product designation Motor management system

design of the product basic unit 3

product type designation SIMOCODE pro V EIP

**General technical data**

product function

? bus communication Yes

? data acquisition function Yes

? diagnostics function Yes

? password protection Yes  
? test function Yes  
? maintenance function Yes  
product component  
? input for thermistor connection Yes  
? digital input Yes  
? input for analog temperature sensors No  
? input for ground fault detection No  
? relay output Yes  
product extension  
? temperature monitoring module Yes  
? current measuring module Yes  
? current/voltage measuring module Yes  
? fail-safe digital I/O module Yes  
? ground-fault monitoring module Yes  
? control unit with display Yes  
? control unit Yes  
? analog I/O module Yes  
consumed active power 3.9 W  
insulation voltage with degree of pollution 3 at AC rated value 300 V  
surge voltage resistance rated value 4 000 V  
protection class IP IP20  
shock resistance  
? according to IEC 60068-2-27 15g / 11 ms  
? vibration resistance 1-6 Hz / 15 mm; 6-500 Hz / 2 g  
switching capacity current of the NO contacts of the relay outputs at AC-15  
? at 24 V 6 A  
? at 120 V 6 A  
? at 230 V 3 A  
switching capacity curr...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3UF7013-1AB00-0 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.