

INDUSTRIAL COMPONENT DATA

3UF7200-1AA01-0 SIEMENS Operator panel titanium gray, installation in control cabinet door or front plate, c..

Brand: SIEMENS | Manufacturer Part Number: 3UF7200-1AA01-0



Manufacturer	SIEMENS
MPN / Reference	3UF7200-1AA01-0
Catalog number	72001
Category	Operator panel for Motor management device
Minimum order	1 Pcs
Document ID	EO-E2412FF6B3
Generated	2026-08-04

Product Overview

Operator panel titanium gray, installation in control cabinet door or front plate, can be plugged onto basic unit or extension modules, 10 LEDs for status display and 5 freely assignable keys for manual control

TITAN GREY CONTROL MODULE; MOUNTING ON CABINET DOOR OR FRONT PANEL; PLUG-IN TO BASE UNIT WITHOUT EXPANSION UNIT; 10 LEDS TO INDICATE STATUS AND 5 ASSIGNABLE BUTTONS FOR MANUAL CONTROL

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > AS-Interface switchgear, SIMOCODE

Additional Product Information

Technical data

Operator panel titanium gray, installation in control cabinet door or front plate, can be plugged onto basic unit or extension modules, 10 LEDs for status display and 5 freely assignable keys for manual control

product brand name SIRIUS

product designation operator panels

General technical data

consumed active power 0.1 W

insulation voltage rated value 300 V

surge voltage resistance rated value 4 000 V

protection class IP on the front IP54

vibration resistance 1-6 Hz / 15 mm; 6-500 Hz / 2 g

reference code according to IEC 81346-2 A

Substance Prohibitance (Date) 07/01/2006

Electromagnetic compatibility

EMC emitted interference according to IEC 60947-1 class A

EMC immunity according to IEC 60947-1 corresponds to degree of severity 3
conducted interference

? due to burst according to IEC 61000-4-4 1 kV

? due to conductor-earth surge according to IEC 61000-4-5 2 kV

? due to conductor-conductor surge according to IEC 61000-4-5 1 kV

field-based interference according to IEC 61000-4-3 10 V/m

Installation/ mounting/ dimensions

mounting position vertical

fastening method front plate mounting

height 36 mm

width 96 mm

depth 44 mm

Ambient conditions

installation altitude at height above sea level

? maximum 4 000 m

? 1 maximum 2 000 m

? 2 maximum 3 000 m; max. +50 °C (no protective separation)

? 3 maximum 4 000 m; max. +40 °C (no protective separation)

ambient temperature

? during operation -25 ... +60 °C

? during storage -40 ... +80 °C

? during transport -40 ... +80 °C

en...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3UF7200-1AA01-0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.