

INDUSTRIAL COMPONENT DATA

3UF7510-1AA00-0 SIEMENS Ground fault module with analog residual current detection for connection of a resid..

Brand: SIEMENS | Manufacturer Part Number: 3UF7510-1AA00-0



Manufacturer	SIEMENS
MPN / Reference	3UF7510-1AA00-0
Catalog number	75101
Category	Extension module for motor management device
Minimum order	1 Pcs
Document ID	EO-32DCA2F930
Generated	2026-08-05

Product Overview

Ground fault module with analog residual current detection for connection of a residual-current transformer 3UL23, max. 1 ground fault module per, for SIMOCODE pro V basic unit

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > CONTROL AND CONTACTORS > AS-Interface switchgear, SIMOCODE
--------------	--

Additional Product Information

Technical data

Ground fault module with analog residual current detection for connection of a residual-current transformer 3UL23, max. 1 ground fault module per, for SIMOCODE pro V basic unit

product brand name SIRIUS

product designation ground fault modules

manufacturer's article number

? 1 of residual current transformer connectable 3UL2302-1A

? 2 of residual current transformer connectable 3UL2303-1A

? 3 of residual current transformer connectable 3UL2304-1A

? 4 of residual current transformer connectable 3UL2305-1A

? 5 of residual current transformer connectable 3UL2306-1A

? 6 of residual current transformer connectable 3UL2307-1A

General technical data

type of current for monitoring AC and pulse-shaped direct currents (type A)

response time maximum 100 ms
product component
? input for thermistor connection No
? input for analog temperature sensors No
? input for ground fault detection Yes
consumed active power 0.1 W
protection class IP IP20
shock resistance according to IEC 60068-2-27 15g / 11 ms
vibration resistance according to IEC 60068-2-6 1 ... 6 Hz: 15 mm, 6 ... 500 Hz: 2g
Substance Prohibitance (Date) 05/01/2012
measurable line frequency initial value 400 Hz
measurable line frequency full-scale value 16 Hz
relative measurement deviation of residual current transformer 2.5 %
Electromagnetic compatibility
EMC emitted interference according to IEC 60947-1 class A
EMC immunity according to IEC 60947-1 corresponds to degree of severity 3
conducted interference
? due t...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3UF7510-1AA00-0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.