

INDUSTRIAL COMPONENT DATA

3UF7600-1AU01-0 SIEMENS Multifunctional module, 4 inputs and 2 relay outputs, input voltage 110-240 V AC/DC ..

Brand: SIEMENS | Manufacturer Part Number: 3UF7600-1AU01-0



Manufacturer	SIEMENS
MPN / Reference	3UF7600-1AU01-0
Catalog number	76001
Category	Extension module for motor management device
Minimum order	1 Pcs
Document ID	EO-66E005B4A5
Generated	2026-08-03

Product Overview

Multifunctional module, 4 inputs and 2 relay outputs, input voltage 110-240 V AC/DC relay outputs monostable, analog residual current detection, with residual-current transformer 3UL23 Connection temperature sensor Pt100/Pt1000/KTY/NTC, max. 1 multifunctional module per basic unit SIMOCODE pro S

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > CONTROL AND CONTACTORS > AS-Interface switchgear, SIMOCODE
--------------	--

Additional Product Information

Technical data

Multifunctional module, 4 inputs and 2 relay outputs, input voltage 110-240 V AC/DC relay outputs monostable, analog residual current detection, with residual-current transformer 3UL23 Connection temperature sensor Pt100/Pt1000/KTY/NTC, max. 1 multifunctional module per basic unit SIMOCODE pro S

product brand name SIRIUS

product designation Multifunction module

manufacturer's article number

? 1 of residual current transformer connectable 3UL2302-1A

? 2 of residual current transformer connectable 3UL2303-1A

? 3 of residual current transformer connectable 3UL2304-1A

? 4 of residual current transformer connectable 3UL2305-1A

? 5 of residual current transformer connectable 3UL2306-1A

? 6 of residual current transformer connectable 3UL2307-1A

General technical data

type of current for monitoring Type A (alternating currents and pulsing DC residual currents)

response time maximum 0.1 s

product function residual current display Yes

adjustable current response value current 40 ... 0.03 A

product component

? input for thermistor connection No

? digital input Yes

? input for residual current converter Yes

? input for analog temperature sensors Yes

? input for ground fault detection Yes

? relay output Yes

consumed active power 0.8 W

insulation voltage with degree of pollution 3 at AC rated value 300 V

surge voltage resistance rated value 4 000 V

protection class IP IP20

shock resistance

? when mounted on current measuring module according to IEC 60068-2-27 10 g / 11 ms

?...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3UF7600-1AU01-0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.