

INDUSTRIAL COMPONENT DATA

3UG4625-1CW30 SIEMENS Digital monitoring relay for residual current monitoring (with current transformer 3UL..

Brand: SIEMENS | Manufacturer Part Number: 3UG4625-1CW30



Manufacturer	SIEMENS
MPN / Reference	3UG4625-1CW30
Catalog number	46251
Category	Residual current monitoring relay
Minimum order	1 Pcs
Document ID	EO-2188CF7BAF
Generated	2026-08-06

Product Overview

Digital monitoring relay for residual current monitoring (with current transformer 3UL23) Setting range 0.03...40 A separate for warning threshold and switch-off value supply voltage 24 ... 240 V AC/DC, 50 .. 60Hz ON delay and tripping delay 0.1 to 20 s Shutdown hysteresis up to 50% Warning hysteresis 5% fixed Width 22.5 mm, 2 change-over contacts with or without fault buffer screw terminal

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > CONTROL AND CONTACTORS > Function relays
--------------	--

Additional Product Information

Technical data

Digital monitoring relay for residual current monitoring (with current transformer 3UL23) Setting range 0.03...40 A separate for warning threshold and switch-off value supply voltage 24 ... 240 V AC/DC, 50 .. 60Hz ON delay and tripping delay 0.1 to 20 s Shutdown hysteresis up to 50% Warning hysteresis 5% fixed Width 22.5 mm, 2 change-over contacts with or without fault buffer screw terminal

product brand name SIRIUS

product designation Residual current monitoring relay with digital setting

product type designation 3UG4

General technical data

product function for three-phase supplies

design of the display LCD

insulation voltage

? rated value 300 V
? for overvoltage category III according to IEC 60664
- with degree of pollution 3 rated value 300 V
degree of pollution 3
type of voltage of the control supply voltage AC/DC
surge voltage resistance rated value 4 kV
protection class IP IP20
? of the enclosure IP20
? of the terminal IP20
shock resistance according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms
vibration resistance according to IEC 60068-2-6 1 ... 6 Hz: 15 mm, 6 ... 500 Hz: 2g
mechanical service life (switching cycles) typical 10 000 000
electrical endurance (switching cycles) at AC-15 at 230 V typical 100 000
thermal current of the switching element with contacts maximum 5 A
reference code according to IEC 81346-2 K
relative repeat accuracy 1 %
Substance Prohibitance (Date) 02/14/2013
Product Function
product function
? residual current display Ye...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3UG4625-1CW30 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.