

INDUSTRIAL COMPONENT DATA

3UG4625-2CW30 SIEMENS Digital monitoring relay for residual current monitoring (with current transformer 3UL..

Brand: SIEMENS | Manufacturer Part Number: 3UG4625-2CW30



Manufacturer	SIEMENS
MPN / Reference	3UG4625-2CW30
Catalog number	46252
Category	Residual current monitoring relay
Minimum order	1 Pcs
Document ID	EO-CDDA9EE356
Generated	2026-08-06

Product Overview

Digital monitoring relay for residual current monitoring (with current transformer 3UL23) Setting range 0.03...40 A separate for warning threshold and switch-off value supply voltage 24 ... 240 V AC/DC, 50 .. 60Hz ON delay and tripping delay 0.1 to 20 s Shutdown hysteresis up to 50% Warning hysteresis 5% fixed Width 22.5 mm, 2 change-over contacts with or without fault buffer spring-type connection system

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Function relays**

Additional Product Information

Technical data

Digital monitoring relay for residual current monitoring (with current transformer 3UL23) Setting range 0.03...40 A separate for warning threshold and switch-off value supply voltage 24 ... 240 V AC/DC, 50 .. 60Hz ON delay and tripping delay 0.1 to 20 s Shutdown hysteresis up to 50% Warning hysteresis 5% fixed Width 22.5 mm, 2 change-over contacts with or without fault buffer spring-type connection system

product brand name SIRIUS

product designation Residual current monitoring relay with digital setting

product type designation 3UG4

General technical data

product function for three-phase supplies

design of the display LCD

insulation voltage

? rated value 300 V
? for overvoltage category III according to IEC 60664
- with degree of pollution 3 rated value 300 V
degree of pollution 3
type of voltage of the control supply voltage AC/DC
surge voltage resistance rated value 4 kV
protection class IP IP20
? of the enclosure IP20
? of the terminal IP20
shock resistance according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms
vibration resistance according to IEC 60068-2-6 1 ... 6 Hz: 15 mm, 6 ... 500 Hz: 2g
mechanical service life (switching cycles) typical 10 000 000
electrical endurance (switching cycles) at AC-15 at 230 V typical 100 000
thermal current of the switching element with contacts maximum 5 A
reference code according to IEC 81346-2 K
relative repeat accuracy 1 %
Substance Prohibitance (Date) 02/14/2013
Product Function
product function
? residual cur...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3UG4625-2CW30 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.