

INDUSTRIAL COMPONENT DATA

3UG4825-2CA40 SIEMENS Digital monitoring relay for residual current monitoring with residual-current transfo..

Brand: SIEMENS | Manufacturer Part Number: 3UG4825-2CA40



Manufacturer	SIEMENS
MPN / Reference	3UG4825-2CA40
Catalog number	48252
Category	Residual current monitoring relay
Minimum order	1 Pcs
Document ID	EO-CBB289F139
Generated	2026-08-06

Product Overview

Digital monitoring relay for residual current monitoring with residual-current transformer 3UL23 for IO-Link Setting range 0.03 A to 40 A separate for warning threshold and switch-off value ON delay and tripping delay 0 to 999.9 s Shutdown hysteresis up to 50% Warning hysteresis 5% fixed Width 22.5mm, 2 change-over contacts with or without fault buffer spring-type connection system

DIGIT SURVEILLANCE RELAYS. P/ VIGIL. CORRIENT. DIFRENCIAL (C/TRANSFORMER INTENS.3UL23) FOR IO-LINK RANGE OF REG. 0.03 TO 40 A SEPARATED FOR ALARM THRESHOLD AND DISCONNECTION THRESHOLD START AND TRIP DELAY 0 TO 999.9S HYSTERESIS DESCON. UP TO 50% HYSTERESIS ALARM 5% FIXED WIDTH 22.5 MM, 2 SWITCHED WITH OR WITHOUT FAULT MEMORY SPRING TERMINALS

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > CONTROL AND CONTACTORS > Function relays
--------------	--

Additional Product Information

Technical data

Digital monitoring relay for residual current monitoring with residual-current transformer 3UL23 for IO-Link Setting range 0.03 A to 40 A separate for warning threshold and switch-off value ON delay and tripping delay 0 to 999.9 s Shutdown hysteresis up to 50% Warning hysteresis 5% fixed Width 22.5mm, 2 change-over contacts with or without fault buffer spring-type connection system

product brand name SIRIUS

product designation Residual current monitoring relay with digital setting

product type designation 3UG4

General technical data

product function for three-phase supplies

design of the display LCD

insulation voltage

? rated value 300 V

? for overvoltage category III according to IEC 60664

- with degree of pollution 3 rated value 300 V

degree of pollution 3

type of voltage of the control supply voltage DC

surge voltage resistance rated value 4 kV

protection class IP IP20

? of the enclosure IP20

? of the terminal IP20

shock resistance according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms

vibration resistance according to IEC 60068-2-6 1 ... 6 Hz: 15 mm, 6 ... 500 Hz: 2g

mechanical service life (switching cycles) typical 10 000 000

electrical endurance (switching cycles) at AC-15 at 230 V typical 100 000

thermal current of the switching element with contacts maximum 5 A

reference code according to IEC 81346-2 K

relative repeat accuracy 1 %

Substance Prohibitance (Date) 02/14/2013

Product Function

product function

? residual current display Yes

? error me...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3UG4825-2CA40 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.