

INDUSTRIAL COMPONENT DATA

3UG4983-1A SIEMENS Voltage reducer module for insulation monitoring relay 3UG4583 for expanding the supply v..

Brand: SIEMENS | Manufacturer Part Number: 3UG4983-1A



Manufacturer	SIEMENS
MPN / Reference	3UG4983-1A
Catalog number	49831
Category	Accessories/spare parts for switching relay
Minimum order	1 Pcs
Document ID	EO-C7AAAD6368
Generated	2026-08-05

Product Overview

Voltage reducer module for insulation monitoring relay 3UG4583 for expanding the supply voltage range to 690 V AC and 1000 V DC screw terminal

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > CONTROL AND CONTACTORS > Function relays
--------------	--

Additional Product Information

Technical data

Voltage reducer module for insulation monitoring relay 3UG4583 for expanding the supply voltage range to 690 V AC and 1000 V DC screw terminal

product brand name SIRIUS

product designation Voltage reducer module

General technical data

product function Converter module

type of voltage

? for monitoring AC/DC

? of the operating voltage for actuation AC/DC

? of the control supply voltage AC/DC

surge voltage resistance rated value 8 000 V

protection class IP IP20

reference code according to IEC 81346-2 K

Substance Prohibitance (Date) 05/01/2012

Measuring circuit

measurable line frequency 15 ... 400 Hz

measurable voltage at AC 690 ... 0 V

Auxiliary circuit

number of NC contacts for auxiliary contacts 0

number of NC contacts delayed switching 0

number of NO contacts for auxiliary contacts 0

number of NO contacts delayed switching 0

number of CO contacts

? delayed switching 0

Main circuit

operating frequency rated value 15 ... 400 Hz

Connections/ Terminals

product component removable terminal for auxiliary and control circuit No

type of electrical connection screw-type terminals

type of connectable conductor cross-sections

? solid 2x (0.75 ... 2.5 mm²)

? finely stranded with core end processing 2x (0.75 ... 2.5 mm²)

connectable conductor cross-section

? solid 0.75 ... 2.5 mm²

? finely stranded with core end processing 0.75 ... 2.5 mm²

AWG number as coded connectable conductor cross section

? solid 20 ... 12

? stranded 18 ... 14

tightening torque with screw-type termin...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3UG4983-1A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.