

INDUSTRIAL COMPONENT DATA

3VA1140-4EF32-0AA0 SIEMENS circuit breaker 3VA1 IEC frame 160 breaking capacity class S Icu 36kA @ 415V 3-po..

Brand: SIEMENS | Manufacturer Part Number: 3VA1140-4EF32-0AA0



Manufacturer	SIEMENS
MPN / Reference	3VA1140-4EF32-0AA0
Catalog number	11404
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-C6C924C74F
Generated	2026-08-05

Product Overview

circuit breaker 3VA1 IEC frame 160 breaking capacity class S Icu=36kA @ 415V 3-pole, line protection TM240, ATAM, In=40A overload protection Ir=28A...40A short-circuit protection Ii=5...10 x In nut keeper kit
AUTOMATIC SWITCH 3VA1 IEC SIZE 160 CUTTING POWER CLASS S ICU=36KA @ 415 V 3 POLES, PROTEC. TM240, ATAM, IN=40A OVERLOAD PROTECTION IR=28A ... 40A SHORT CIRCUIT PROTECTION II=5...10 X IN FLAT CONNECTION WITH SCREW. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Moulded Case Circuit Breakers 3VA S

Additional Product Information

Technical data

circuit breaker 3VA1 IEC frame 160 breaking capacity class S Icu=36kA @ 415V 3-pole, line protection TM240, ATAM, In=40A overload protection Ir=28A...40A short-circuit protection Ii=5...10 x In nut keeper kit

Model

product brand name SENTRON

product designation Molded case circuit breaker

Product version Line protection

design of the overcurrent release TM240

protection function of the overcurrent release LI

number of poles 3

General technical data

rated insulation voltage U_i 800 V
Max. rated operational voltage U_e with DC 500 V
power loss [W] / maximum 10.8 W
Active power loss / for rated value of the current / at AC / in hot operating state / per pole 3.6 W
mechanical service life (switching cycles) / typical 20 000
Electrical endurance (switching cycles) / at AC-1 / at 380/415 V 50/60 Hz 9 000
Electrical endurance (switching cycles) / at AC-1 / at 690 V 50/60 Hz 6 300
Neutral conductors / upgradeable/retrofittable No
ground-fault monitoring version Without
product function
? communication function No
? other measurement function No
Net Weight 960 g
Current
Max. rated operational current of the frame size 160 A
Courant permanent assigné I_u 40 A
operational current
? at 40 °C 40 A
? at 45 °C 40 A
? at 50 °C 40 A
? at 55 °C 39 A
? at 60 °C 39 A
? at 65 °C 38 A
? at 70 °C 37 A
Switching capacity according to IEC 60947
switching capacity class of the circuit breaker S
breaking capacity maximum short-circuit current (I_{cu})
? at 240 V 55 kA
? at 415 V 36 kA
? at 44...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3VA1140-4EF32-0AA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.