

INDUSTRIAL COMPONENT DATA

3VA2110-8KQ46-0AA0 SIEMENS circuit breaker 3VA2 IEC Frame 160 breaking capacity class L Icu 150 kA @ 415 V 4..

Brand: SIEMENS | Manufacturer Part Number: 3VA2110-8KQ46-0AA0



Manufacturer	SIEMENS
MPN / Reference	3VA2110-8KQ46-0AA0
Catalog number	21108
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-52F43F1E64
Generated	2026-08-05

Product Overview

circuit breaker 3VA2 IEC Frame 160 breaking capacity class L Icu=150 kA @ 415 V 4-pole, line protection ETU860, LSIG, In=100 A overload protection Ir=40 A...100 A short-circuit protection Isd=0.6..10x In, li=1.5..12x In neutral conductor protection adjustable (OFF, up to 160%) ground-fault protection, can be switched off Ig=0.2...1 x In= tg=0.05-0.8s terminal connection

AUTOM SWITCH. 3VA2 IEC SIZE 160 CUTTING POWER CLASS L ICU=150KA @ 415 V 4 POLOS, PROTEC. DISTRIBUTIONS ETU860, LSIG, IN=100A OVERLOAD PROTECTION IR=40A ... 100A SHORT CIRCUIT PROTECTION ISD=0,6..10X IN, II=1,5..12X IN PROT. ADJUSTABLE NEUTRAL (OFF, UP TO 160%) PROT. DEFECT TO EARTH, DESCON. GI=0.2... 1 X IN, TG=0.05-0.8MS CONNECTION BY BORNE. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Moulded Case Circuit Breakers 3VA S

Additional Product Information

Product

Article Number (Market Facing Number) 3VA2110-8KQ46-0AA0

Product Description circuit breaker 3VA2 IEC Frame 160 breaking capacity class L Icu=150 kA @ 415 V 4-pole, line protection ETU860, LSIG, In=100 A overload protection Ir=40 A...100 A short-circuit protection Isd=0.6..10x In, li=1.5..12x In neutral conductor protection adjustable (OFF, up to 160%) ground-fault protection, can be switched off Ig=0.2...1 x In= tg=0.05-0.8s terminal connection

Product family 3VA Molded Case Circuit Breakers up to 1600 A, IEC

Product Lifecycle (PLM) PM300:Active Product

Price data

Region Specific PriceGroup / Headquarter Price Group 12P / 53K

Surcharge for Raw Materials None

Metal Factor LOA-----

Delivery information

Export Control Regulations AL : N / ECCN : 9N9999

Standard lead time ex-works 10 Day/Days

Net Weight (kg) 3,200 Kg

Packaging Dimension 169,00 x 200,00 x 145,00

Package size unit of measure MM

Quantity Unit 1 Piece

Packaging Quantity 1

Additional Product Information

EAN 4042948819739

UPC 804766439766

Commodity Code 85362090

LKZ_FDB/ CatalogID LV10.1

Product Group 5374

Group Code P360

Country of origin Czech Republic

Compliance with the substance restrictions according to RoHS directive Since: 01.06.2012

Product class C: products manufactured / produced to order, which cannot be reused or re-utilized or be returned against credit.

WEEE (2012/19/EU) Take-Back Obligation Yes

REACH Art. 33 Duty to inform according to the current list of candidates Lead CAS-No. 7439-92-1 > 0,...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3VA2110-8KQ46-0AA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.