

INDUSTRIAL COMPONENT DATA

3VA2125-5KQ32-0AA0 SIEMENS circuit breaker 3VA2 IEC Frame 160 breaking capacity class M Icu 55 kA @ 415 V 3-..

Brand: SIEMENS | Manufacturer Part Number: 3VA2125-5KQ32-0AA0



Manufacturer	SIEMENS
MPN / Reference	3VA2125-5KQ32-0AA0
Catalog number	21255
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-F34839CAB6
Generated	2026-08-06

Product Overview

circuit breaker 3VA2 IEC Frame 160 breaking capacity class M Icu=55 kA @ 415 V 3-pole, line protection ETU860, LSIG, In=25 A overload protection Ir=10 A...25 A short-circuit protection Isd=0.6..10x In, Ii=1.5..12x In neutral conductor protection optionally with external current transformer, up to 160% ground-fault protection, can be switched off Ig=0.2...1 x In, tg=0.05-0.8s nut keeper kit

AUTOM SWITCH. 3VA2 IEC SIZE 160 CUTTING POWER CLASS M ICU=55KA @ 415 V 3 POLES, PROTEC. DISTRIBUTIONS ETU860, LSIG, IN=25A OVERLOAD PROTECTION IR=10A ... 25A SHORT CIRCUIT PROTECTION ISD=0,6..10X IN, II=1,5..12X IN PROT. OPTIONAL NEUTRAL WITH TC EXT.,UP TO 160% PROT. DEFECT TO EARTH, DESCON. GI=0.2... 1 X IN, TG=0.05-0.8MS CONEX. BY PLATE AND SCREW. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Moulded Case Circuit Breakers 3VA S

Additional Product Information

Product

Article Number (Market Facing Number) 3VA2125-5KQ32-0AA0

Product Description circuit breaker 3VA2 IEC Frame 160 breaking capacity class M Icu=55 kA @ 415 V 3-pole, line protection ETU860, LSIG, In=25 A overload protection Ir=10 A...25 A short-circuit protection Isd=0.6..10x In, Ii=1.5..12x In neutral conductor protection optionally with external current transformer, up to 160% ground-fault protection, can be switched off Ig=0.2...1 x In, tg=0.05-0.8s nut keeper kit

Product family 3VA Molded Case Circuit Breakers up to 1600 A, IEC

Product Lifecycle (PLM) PM300:Active Product

Price data

Region Specific PriceGroup / Headquarter Price Group 12P / 53K

Surcharge for Raw Materials None

Metal Factor LOA-----

Delivery information

Export Control Regulations AL : N / ECCN : 9N9999

Standard lead time ex-works 5 Day/Days

Net Weight (kg) 2,500 Kg

Packaging Dimension 134,00 x 200,00 x 145,00

Package size unit of measure MM

Quantity Unit 1 Piece

Packaging Quantity 1

Additional Product Information

EAN 4042948801840

UPC 804766438554

Commodity Code 85362010

LKZ_FDB/ CatalogID LV10.1

Product Group 5374

Group Code P360

Country of origin Czech Republic

Compliance with the substance restrictions according to RoHS directive Since: 01.06.2012

Product class C: products manufactured / produced to order, which cannot be reused or re-utilized or be returned against credit.

WEEE (2012/19/EU) Take-Back Obligation Yes

REACH Art. 33 Duty to inform according to the current list of candidates Lead CAS...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3VA2125-5KQ32-0AA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.