

**INDUSTRIAL COMPONENT DATA**

# 3VA5190-4ED31-0AA0 SIEMENS circuit breaker 3VA5 UL Frame 125 breaking capacity class S 25 kA @ 480 V 3-pole,..

Brand: SIEMENS | Manufacturer Part Number: 3VA5190-4ED31-0AA0



|                 |                                                                   |
|-----------------|-------------------------------------------------------------------|
| Manufacturer    | SIEMENS                                                           |
| MPN / Reference | 3VA5190-4ED31-0AA0                                                |
| Catalog number  | 10000                                                             |
| Category        | Power circuit-breaker for trafo/generator/installation protection |
| Minimum order   | 1 Pcs                                                             |
| Document ID     | EO-88441129CD                                                     |
| Generated       | 2026-08-04                                                        |

## Product Overview

circuit breaker 3VA5 UL Frame 125 breaking capacity class S 25 kA @ 480 V 3-pole, line protection TM210, FTFM, In=90 A overload protection Ir=90 A permanently set short-circuit protection li=10 x In without connection  
AUTOMATIC SWITCH 3VA5 UL size 125 CUTTING POWER CLASS S 25KA @ 480 V 3 POLES, PROTEC. TM210, FTFM, IN=90A OVERLOAD PROTECTION IR=90A FIXEDLY ADJUSTED SHORT-CIRCUIT PROTECTION II=10 X IN WITHOUT ELEMENT. OF CONNECTION. Manufactured to order. Non-Cancelable Non-Returnable.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path

SIEMENS &gt; POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR &gt; Moulded Case Circuit Breakers 3VA S

## Additional Product Information

**Product**

Article Number (Market Facing Number) 3VA5190-4ED31-0AA0

Product Description circuit breaker 3VA5 UL Frame 125 breaking capacity class S 25 kA @ 480 V 3-pole, line protection TM210, FTFM, In=90 A overload protection Ir=90 A permanently set short-circuit protection li=10 x In without connection

Product family 3VA Moulded Case Circuit Breakers up to 2000 A, UL / IEC

Product Lifecycle (PLM) PM300:Active Product

**Price data**

Region Specific PriceGroup / Headquarter Price Group 12P / 53H

Surcharge for Raw Materials None

Metal Factor LOA-----

**Delivery information**

Export Control Regulations AL : N / ECCN : EAR99

Standard lead time ex-works 30 Day/Days

Net Weight (kg) 0,960 Kg

Packaging Dimension 92,00 x 150,00 x 116,00

Package size unit of measure MM

Quantity Unit 1 Piece

Packaging Quantity 1

Additional Product Information

EAN 4042948841242

UPC 804766300943

Commodity Code 85362090

LKZ\_FDB/ CatalogID LV10

Product Group 5385

Group Code P360

Country of origin Mexico

Compliance with the substance restrictions according to RoHS directive Since: 01.01.2016

Product class C: products manufactured / produced to order, which cannot be reused or re-utilized or be returned against credit.

WEEE (2012/19/EU) Take-Back Obligation Yes

REACH Art. 33 Duty to inform according to the current list of candidates Lead CAS-No. 7439-92-1 > 0, 1 % (w /

w)Information obligation imposed by Article 33, REACH Regulation: This product includes one or several articles in which the following substance of the....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3VA5190-4ED31-0AA0 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.