

## INDUSTRIAL COMPONENT DATA

# 3VA5220-6EC61-0AA0 SIEMENS circuit breaker 3VA5 UL Frame 250 breaking capacity class H 65 kA @ 480 V 2-pole,...

Brand: SIEMENS | Manufacturer Part Number: 3VA5220-6EC61-0AA0



|                 |                                                                   |
|-----------------|-------------------------------------------------------------------|
| Manufacturer    | SIEMENS                                                           |
| MPN / Reference | 3VA5220-6EC61-0AA0                                                |
| Catalog number  | 10000                                                             |
| Category        | Power circuit-breaker for trafo/generator/installation protection |
| Minimum order   | 1 Pcs                                                             |
| Document ID     | EO-1BDC464E35                                                     |
| Generated       | 2026-08-05                                                        |

## Product Overview

circuit breaker 3VA5 UL Frame 250 breaking capacity class H 65 kA @ 480 V 2-pole, line protection TM230, FTAM, In=200 A overload protection Ir=200 A permanently set short-circuit protection li=5...10 x In without connection  
AUTOMATIC SWITCH 3VA5 UL size 250 CUTTING POWER CLASS H 65KA @ 480 V 2 POLES, PROTEC. TM230, FTAM, IN=200A OVERLOAD PROTECTION IR=200A FIXED SET SHORT CIRCUIT PROTECTION II=5...10 X IN WITHOUT ELEMENT. OF CONNECTION. Manufactured to order. Non-Cancelable Non-Returnable.

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path

SIEMENS &gt; POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR &gt; Moulded Case Circuit Breakers 3VA S

## Additional Product Information

## Product

Article Number (Market Facing Number) 3VA5220-6EC61-0AA0

Product Description circuit breaker 3VA5 UL Frame 250 breaking capacity class H 65 kA @ 480 V 2-pole, line protection TM230, FTAM, In=200 A overload protection Ir=200 A permanently set short-circuit protection li=5...10 x In without connection

Product family 3VA Molded Case Circuit Breakers up to 2000 A, UL / IEC

Product Lifecycle (PLM) PM300:Active Product

## Price data

Region Specific PriceGroup / Headquarter Price Group 12P / 53H

Surcharge for Raw Materials None

Metal Factor LOA-----

**Delivery information**

Export Control Regulations AL : N / ECCN : 9N9999

Standard lead time ex-works 10 Day/Days

Net Weight (kg) 1,782 Kg

Packaging Dimension 150,00 x 245,00 x 160,00

Package size unit of measure MM

Quantity Unit 1 Piece

Packaging Quantity 1

**Additional Product Information**

EAN 4042948853740

UPC 804766308338

Commodity Code 85362090

LKZ\_FDB/ CatalogID LV10

Product Group 5385

Group Code P360

Country of origin Czech Republic

Compliance with the substance restrictions according to RoHS directive Since: 01.01.2016

Product class C: products manufactured / produced to order, which cannot be reused or re-utilized or be returned against credit.

WEEE (2012/19/EU) Take-Back Obligation Yes

REACH Art. 33 Duty to inform according to the current list of candidates Reach Information There is currently no information on SVHC (Substances of Very High Concern <http://echa.europa.eu/web/guest/candidate-list-table>) from the supply chain and o...**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**Send SIEMENS / 3VA5220-6EC61-0AA0 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](http://electricaonline.com/request-quote).**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.