

INDUSTRIAL COMPONENT DATA

3VA6140-7JQ31-0AA0 SIEMENS circuit breaker 3VA6 UL Frame 150 breaking capacity class C 100 kA @ 480 V 3-pole..

Brand: SIEMENS | Manufacturer Part Number: 3VA6140-7JQ31-0AA0



Manufacturer	SIEMENS
MPN / Reference	3VA6140-7JQ31-0AA0
Catalog number	10000
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-480EF604E7
Generated	2026-08-06

Product Overview

circuit breaker 3VA6 UL Frame 150 breaking capacity class C 100 kA @ 480 V 3-pole, line protection ETU560, LSIG, In=40 A overload protection Ir=16 A...40 A short-circuit protection Isd=0.6..10x In, li=1.5..12x In neutral conductor protection optionally with external current transformer, up to 160% ground-fault protection Ig=0.375...1 x In, tg=0.05-0.8s without connection

AUTOMATIC SWITCH 3VA6 UL size 150 CUTTING POWER CLASS C 100KA @ 480 V 3 POLES, PROTEC. DISTRIBUTIONS ETU560, LSIG, IN=40A OVERLOAD PROTECTION IR=16A ... 40A SHORT CIRCUIT PROTECTION ISD=0.6..10X IN, II=1.5..12X IN NEUTRAL OPC PROTECTION. WITH TC EXT., UP TO 160% GROUND DEFECT PROTECTION IG=0.375...1X IN, TG=0.05-0.8S WITHOUT ELEMENT. OF CONNECTION. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Moulded Case Circuit Breakers 3VA S

Additional Product Information

Product

Article Number (Market Facing Number) 3VA6140-7JQ31-0AA0

Product Description circuit breaker 3VA6 UL Frame 150 breaking capacity class C 100 kA @ 480 V 3-pole, line protection ETU560, LSIG, In=40 A overload protection Ir=16 A...40 A short-circuit protection Isd=0.6..10x In, li=1.5..12x In neutral conductor protection optionally with external current transformer, up to 160% ground-fault protection Ig=0.375...1 x In, tg=0.05-0.8s without connection

Product family 3VA Molded Case Circuit Breakers up to 2000 A, UL / IEC

Product Lifecycle (PLM) PM300:Active Product

Price data

Region Specific PriceGroup / Headquarter Price Group 12P / 53H

Surcharge for Raw Materials None

Metal Factor LOA-----

Delivery information

Export Control Regulations AL : N / ECCN : 9N9999

Standard lead time ex-works 5 Day/Days

Net Weight (kg) 2,500 Kg

Packaging Dimension 134,00 x 200,00 x 145,00

Package size unit of measure MM

Quantity Unit 1 Piece

Packaging Quantity 1

Additional Product Information

EAN 4042948847893

UPC 804766303395

Commodity Code 85362010

LKZ_FDB/ CatalogID LV10

Product Group 5383

Group Code P360

Country of origin Czech Republic

Compliance with the substance restrictions according to RoHS directive Since: 01.01.2016

Product class C: products manufactured / produced to order, which cannot be reused or re-utilized or be returned against credit.

WEEE (2012/19/EU) Take-Back Obligation Yes

REACH Art. 33 Duty to inform according to the current list of candidates Lead CAS-No. 7439-92-1 >...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3VA6140-7JQ31-0AA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.