

INDUSTRIAL COMPONENT DATA

3VA9112-0JF60 SIEMENS distribution wire connector 6 cables 2 units accessory for: 3VA1 160

Brand: SIEMENS | Manufacturer Part Number: 3VA9112-0JF60



Manufacturer	SIEMENS
MPN / Reference	3VA9112-0JF60
Catalog number	91120
Category	Accessories/spare parts for low-voltage switch technology
Minimum order	1 Pcs
Document ID	EO-181F22AF7F
Generated	2026-08-03

Product Overview

distribution wire connector 6 cables 2 units accessory for: 3VA1 160

ROUND CONDUCTOR TERMINAL 6 CABLES 2 PCS ACCESSORY FOR: 3VA1 160. Cancellations and returns limited. Consult conditions.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Moulded Case Circuit Breakers 3VA S

Additional Product Information

Technical data

distribution wire connector 6 cables 2 units accessory for: 3VA1 160

Model

product brand name SENTRON

product designation accessories

Accessories Wire connector

General technical data

designation / of the terminal TA2.5

Connections according IEC

connectable conductor cross-section

? for copper cable / stranded / minimum 1.5 mm²

? for copper cable / stranded / maximum 35 mm²

? for aluminum cable / solid / minimum 4 mm²

? for aluminum cable / solid / maximum 16 mm²
? for aluminum cable / stranded / minimum 4 mm²
? for aluminum cable / stranded / maximum 35 mm²
stripped length 12 / 24 / 39.5 mm
tightening torque / when using copper cables
? solid 1.5 mm²: 2.8 Nm, 2.5 - 10 mm²: 6.2 Nm 16 mm²: 7 Nm
Connections according UL
permissible temperature / of connectable conductor / according to UL 486A-486B 75 °C
connectable conductor cross-section
? for copper cable / solid / minimum 14 AWG
? for copper cable / solid / maximum 10 AWG
? for copper cable / stranded / minimum 14 AWG
? for copper cable / stranded / maximum 2 AWG
? for copper cable / finely stranded / minimum 14 AWG
? for copper cable / finely stranded / maximum 2 AWG
? for copper cable / finely stranded / with core end processing / maximum 25
? for aluminum cable / solid / minimum 12 AWG
? for aluminum cable / solid / maximum 10 AWG
? for aluminum cable / stranded / minimum 12 AWG
? for aluminum cable / stranded / maximum 2 AWG
tightening torque / when using copper cables
? stranded 14 - 8 AWG: 55 lb-in, 6 - 2...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3VA9112-0JF60 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.