


INDUSTRIAL COMPONENT DATA

3VA9243-0JK12 SIEMENS wire connector CU with control wire voltage tap-off 3 units accessory for: 3VA6 150/250

Brand: SIEMENS | Manufacturer Part Number: 3VA9243-0JK12



Manufacturer	SIEMENS
MPN / Reference	3VA9243-0JK12
Catalog number	92430
Category	Accessories/spare parts for low-voltage switch technology
Minimum order	1 Pcs
Document ID	EO-271841E707
Generated	2026-08-06

Product Overview

wire connector CU with control wire voltage tap-off 3 units accessory for: 3VA6 150/250
 TERMINAL FOR ROUND CONDUCTOR CU WITH POWER SOCKET. AUX DRIVER. 3 ACCESSORY UNITS FOR: 3VA6 150/250. Cancellations and returns limited. Consult conditions.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Moulded Case Circuit Breakers 3VA S**

Additional Product Information

Technical data

wire connector CU with control wire voltage tap-off 3 units accessory for: 3VA6 150/250

Model

product brand name SENTRON

product designation accessories

Product version circular conductor terminal

Accessories Wire connector

General technical data

designation / of the terminal TC1.4

Connections according IEC

stripped length 20 mm

Connetctions according UL

permissible temperature / of connectable conductor / according to UL 486A-486B 90 °C

stripped length 0.8 in

connectable conductor cross-section

? for copper cable / stranded / minimum 6 AWG

? for copper cable / stranded / maximum 350 kcmil

? for copper cable / finely stranded / minimum 6 AWG

? for copper cable / finely stranded / maximum 350 kcmil

tightening torque / when using copper cables

? stranded 6 - 2 AWG: 140 lb-in, 1 AWG - 350 kcmil: 275 lb-in

Downloads and manuals

? finely stranded 6 - 2 AWG: 140 lb-in, 1 AWG - 350 kcmil: 275 lb-in

Further information

Information- and Downloadcenter (Catalogs, Brochures,...) <http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system) <https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA9243-0JK12>

Service&Support (Manuals, Certificates, Characteristics,

FAQs,...) <https://support.industry.siemens.com/cs/ww/en/ps/3VA9243-0JK12>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams,

...) http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA9243-0JK12

CAX-Online-Generator <http://www.siemens.com/cax>

Te...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3VA9243-0JK12 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.