

INDUSTRIAL COMPONENT DATA

3VA9264-0JB12 SIEMENS wire connector 4 units accessory for: 3VA2 100/160/250

Brand: SIEMENS | Manufacturer Part Number: 3VA9264-0JB12



Manufacturer	SIEMENS
MPN / Reference	3VA9264-0JB12
Catalog number	92640
Category	Accessories/spare parts for low-voltage switch technology
Minimum order	1 Pcs
Document ID	EO-BE1D07D07A
Generated	2026-08-05

Product Overview

wire connector 4 units accessory for: 3VA2 100/160/250

BORNE P. ROUND CONDUCTOR 4 PC. ACCESSORY FOR: 3VA2 100/160/250. Cancellations and returns limited. Consult conditions.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Moulded Case Circuit Breakers 3VA S**

Additional Product Information

Technical data

wire connector 4 units accessory for: 3VA2 100/160/250

Model

product brand name SENTRON

product designation accessories

Accessories Wire connector

General technical data

designation / of the terminal TA1.4

Connections according IEC

connectable conductor cross-section

? for copper cable / stranded / minimum 16 mm²

? for copper cable / stranded / maximum 185 mm²

? for aluminum cable / solid / minimum 16 mm²

? for aluminum cable / solid / maximum 16 mm²
? for aluminum cable / stranded / minimum 16 mm²
? for aluminum cable / stranded / maximum 185 mm²
stripped length 20 mm
tightening torque / when using copper cables
? solid 16 mm²: 15.8 Nm
Connections according UL
permissible temperature / of connectable conductor / according to UL 486A-486B 75 °C
stripped length 0.8 in
connectable conductor cross-section
? for copper cable / stranded / minimum 6 AWG
? for copper cable / stranded / maximum 350 kcmil
? for copper cable / finely stranded / minimum 6 AWG
? for copper cable / finely stranded / maximum 350 kcmil
? for copper cable / finely stranded / with core end processing / minimum 16
? for copper cable / finely stranded / with core end processing / maximum 120
? for aluminum cable / stranded / minimum 6 AWG
? for aluminum cable / stranded / maximum 350 kcmil
tightening torque / when using copper cables
? stranded 6 - 2 AWG: 140 lb-in, 1 AWG - 350 kcmil: 275 lb-in
Downloads and manuals
? finely stranded 6 - 2 AWG: 140 lb-in, 1 AWG - 350 kcmil: 275 lb-in
Further info...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3VA9264-0JB12 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.