

## INDUSTRIAL COMPONENT DATA

## 3VA9384-0JG13 SIEMENS wire connector with control wire voltage tap-off 4 units accessory for: 3VA1 400/630 3..

Brand: SIEMENS | Manufacturer Part Number: 3VA9384-0JG13



|                 |                                                           |
|-----------------|-----------------------------------------------------------|
| Manufacturer    | SIEMENS                                                   |
| MPN / Reference | 3VA9384-0JG13                                             |
| Catalog number  | 93840                                                     |
| Category        | Accessories/spare parts for low-voltage switch technology |
| Minimum order   | 1 Pcs                                                     |
| Document ID     | EO-FD9A57D8E5                                             |
| Generated       | 2026-08-04                                                |

### Product Overview

wire connector with control wire voltage tap-off 4 units accessory for: 3VA1 400/630 3VA2 400/630  
TERMINAL FOR ROUND CONDUCTOR WITH VOLTAGE CONDUCTION TAKEOVER. AUX. 4 PC. ACCESSORY FOR:  
3VA2 400/630. Cancellations and returns limited. Consult conditions.

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path

SIEMENS &gt; POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR &gt; Moulded Case Circuit Breakers 3VA S

### Additional Product Information

## Technical data

wire connector with control wire voltage tap-off 4 units accessory for: 3VA1 400/630 3VA2 400/630

## Model

product brand name SENTRON

product designation accessories

Accessories Wire connector

## General technical data

designation / of the terminal TA1.5

Connections according IEC

connectable conductor cross-section

? for copper cable / stranded / minimum 50 mm<sup>2</sup>

? for copper cable / stranded / maximum 300 mm<sup>2</sup>

? for aluminum cable / stranded / minimum 50 mm<sup>2</sup>

? for aluminum cable / stranded / maximum 300 mm<sup>2</sup>

stripped length 28 mm

Connetctions according UL

permissible temperature / of connectable conductor / according to UL 486A-486B 75 °C

stripped length 1.1 in

connectable conductor cross-section

? for copper cable / stranded / minimum 1 AWG

? for copper cable / stranded / maximum 600 kcmil

? for copper cable / finely stranded / minimum 1 AWG

? for copper cable / finely stranded / maximum 600 kcmil

? for copper cable / finely stranded / with core end processing / minimum 50

? for copper cable / finely stranded / with core end processing / maximum 240

? for aluminum cable / stranded / minimum 1 AWG

? for aluminum cable / stranded / maximum 600 kcmil

tightening torque / when using copper cables

? stranded 1 AWG - 600 kcmil: 375 lb-in

Downloads and manuals

? finely stranded 1 AWG - 600 kcmil: 375 lb-in

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)<https://mall.ind...>

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3VA9384-0JG13 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.