

INDUSTRIAL COMPONENT DATA

3VA9384-0JG13 SIEMENS wire connector with control wire voltage tap-off 4 units accessory for: 3VA1 400/630 3..

Brand: SIEMENS | Manufacturer Part Number: 3VA9384-0JG13



Manufacturer	SIEMENS
MPN / Reference	3VA9384-0JG13
Catalog number	93840
Category	Accessories/spare parts for low-voltage switch technology
Minimum order	1 Pcs
Document ID	EO-FD9A57D8E5
Generated	2026-08-05

Product Overview

wire connector with control wire voltage tap-off 4 units accessory for: 3VA1 400/630 3VA2 400/630
 TERMINAL FOR ROUND CONDUCTOR WITH VOLTAGE CONDUCTION TAKEOVER. AUX. 4 PC. ACCESSORY FOR:
 3VA2 400/630. Cancellations and returns limited. Consult conditions.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Moulded Case Circuit Breakers 3VA S**

Additional Product Information

Technical data

wire connector with control wire voltage tap-off 4 units accessory for: 3VA1 400/630 3VA2 400/630

Model

product brand name SENTRON

product designation accessories

Accessories Wire connector

General technical data

designation / of the terminal TA1.5

Connections according IEC

connectable conductor cross-section

? for copper cable / stranded / minimum 50 mm²

? for copper cable / stranded / maximum 300 mm²

? for aluminum cable / stranded / minimum 50 mm²

? for aluminum cable / stranded / maximum 300 mm²

stripped length 28 mm

Connetctions according UL

permissible temperature / of connectable conductor / according to UL 486A-486B 75 °C

stripped length 1.1 in

connectable conductor cross-section

? for copper cable / stranded / minimum 1 AWG

? for copper cable / stranded / maximum 600 kcmil

? for copper cable / finely stranded / minimum 1 AWG

? for copper cable / finely stranded / maximum 600 kcmil

? for copper cable / finely stranded / with core end processing / minimum 50

? for copper cable / finely stranded / with core end processing / maximum 240

? for aluminum cable / stranded / minimum 1 AWG

? for aluminum cable / stranded / maximum 600 kcmil

tightening torque / when using copper cables

? stranded 1 AWG - 600 kcmil: 375 lb-in

Downloads and manuals

? finely stranded 1 AWG - 600 kcmil: 375 lb-in

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)<https://mall.ind...>

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3VA9384-0JG13 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.