

INDUSTRIAL COMPONENT DATA

3VA9988-0AA23 SIEMENS LEADING CHANGEOVER SWITCH CHANGEOVER CONTACTS TYPE HQ (7MM) ELECTRONIC ACCESSORY FOR 3..

Brand: SIEMENS | Manufacturer Part Number: 3VA9988-0AA23



Manufacturer	SIEMENS
MPN / Reference	3VA9988-0AA23
Catalog number	99880
Category	Accessories/spare parts for low-voltage switch technology
Minimum order	1 Pcs
Document ID	EO-13A5DA680C
Generated	2026-08-04

Product Overview

LEADING CHANGEOVER SWITCH CHANGEOVER CONTACTS TYPE HQ (7MM) ELECTRONIC ACCESSORY FOR 3VA1 and 3VA20 up to 3VA25
CONTAC BLOCK. AUX. ADVANCE. SWITCHED CONTACTS TYPE HQ (7MM) ELECTRONIC. ACCESSORY FOR: 3VA SWITCH. Cancellations and returns limited. Consult conditions.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Moulded Case Circuit Breakers 3VA S

Additional Product Information

Technical data

LEADING CHANGEOVER SWITCH CHANGEOVER CONTACTS TYPE HQ (7MM) ELECTRONIC ACCESSORY FOR 3VA1 and 3VA20 up to 3VA25

Model

product brand name SENTRON

product designation Leading auxiliary switch

Product version Accessories for 3VA circuit breakers

Accessories Leading auxiliary switch

General technical data

Degree of pollution 3

Overvoltage category III

lead time / relating to main contacts 20 ms

Voltage

Tension assignée de tenue aux chocs 4 kV

Rated operational voltage Ue at AC 50 Hz 24 V

Rated operational voltage Ue with DC 24 V

Current

Thermal current limit Ith 0.3 A

operational current

? at AC-12 / at 12 V 0.3 A

? at AC-12 / at 24 V 0.3 A

? at DC-12 / at 12 V 0.1 A

? at DC-12 / at 24 V 0.1 A

? at DC-13 / at 12 V 0.07 A

? at DC-13 / at 24 V 0.07 A

? at AC-15 / at 12 V 0.3 A

? at AC-15 / at 24 V 0.3 A

Mechanical Design

Height 56 mm

Width 7 mm

depth 30 mm

net weight 30 g

tightening torque / with screw-type terminals / minimum 0.4 N·m

tightening torque / with screw-type terminals / maximum 0.5 N·m

Connections according IEC

stripped length 15 mm

AWG number / as coded connectable conductor cross section / for auxiliary contacts

? minimum 20

? maximum 16

Connetctions according UL

stripped length [in] 0.6 in

tightening torque [lbf·in] / with screw-type terminals / minimum 3.5 lbf·in

Downloads and manuals

tightening torque [lbf·in] / with screw-type terminals / maximum 4.4 lbf·in

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)<http://www.siemens.com>

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3VA9988-0AA23 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.