

INDUSTRIAL COMPONENT DATA

3VL2506-1VM30-0AA0 SIEMENS CIRCUIT-BREAKER VL 150 UL TYPE DG (CAT NO. NDK3G060) NON-INTERCHANGEABLE FRAME W...

Brand: SIEMENS | Manufacturer Part Number: 3VL2506-1VM30-0AA0



Manufacturer	SIEMENS
MPN / Reference	3VL2506-1VM30-0AA0
Catalog number	25061
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-E0FB7D03AF
Generated	2026-08-06

Product Overview

CIRCUIT-BREAKER VL 150 UL TYPE DG (CAT NO. NDK3G060) NON-INTERCHANGEABLE FRAME W. APPROBATION CIRCUIT-BREAKER ACC. UL489 STANDARD SWITCHING CAPACITY 3-POLE, NEMA RATING 35KA@480V AND 18KA@600/347V (MOLDED CASE CIRCUIT BREAKER) OVERCURRENT RELEASE LCD ETU, LSIG TU= 40 DEGR. CELSIUS 3 PHASES/4 CABLES IN=60A, RATED CURRENT ISD=1,25-10 X IR, II=11X IN SHORT-CIRCUIT PROTECTION IR=30-60A OVERCURRENT REL. F. PLANT PROTECTION W/O CONNECTION ACCESSORIES WITHOUT AUXILIARY/ALARM SWITCH

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Moulded Case Circuit Breakers 3VL S

Additional Product Information

Product

Article Number (Market Facing Number) 3VL2506-1VM30-0AA0

Product Description CIRCUIT-BREAKER VL 150 UL TYPE DG (CAT NO. NDK3G060) NON-INTERCHANGEABLE FRAME W. APPROBATION CIRCUIT-BREAKER ACC. UL489 STANDARD SWITCHING CAPACITY 3-POLE, NEMA RATING 35KA@480V AND 18KA@600/347V (MOLDED CASE CIRCUIT BREAKER) OVERCURRENT RELEASE LCD ETU, LSIG TU= 40 DEGR. CELSIUS 3 PHASES/4 CABLES IN=60A, RATED CURRENT ISD=1,25-10 X IR, II=11X IN SHORT-CIRCUIT PROTECTION IR=30-60A OVERCURRENT REL. F. PLANT PROTECTION W/O CONNECTION ACCESSORIES WITHOUT AUXILIARY/ALARM SWITCH

Product family Ordering Data Overview

Product Lifecycle (PLM) PM300:Active Product

Price data

Price Group / Headquarter Price Group 33A / 1CC

List Price Show prices

Customer Price Show prices

Metal Factor LBO-----

Delivery information

Export Control Regulations AL : N / ECCN : EAR99

Standard lead time ex-works 5 Day/Days

Net Weight (kg) 2,400 Kg

Product Dimensions (W x L x H) Not available

Packaging Dimension Not available

Package size unit of measure Not available

Quantity Unit 1 Piece

Packaging Quantity 1

Additional Product Information

EAN Not available

UPC 887621132590

Commodity Code 85362010

LKZ_FDB/ CatalogID LV10.1

Product Group 3742

Country of origin Germany

Compliance with the substance restrictions according to RoHS directive Since: 06/09/11

Product class C: products manufactured / produced to order, which cannot be reused or re-utilised or be returned against credit.

Obligation Category for taking back electric...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3VL2506-1VM30-0AA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.