

INDUSTRIAL COMPONENT DATA

3VL2710-2SP36-0AA0 SIEMENS circuit breaker VL160H high breaking capacity Icu 70kA, 415V AC 3-pole, motor/gen..

Brand: SIEMENS | Manufacturer Part Number: 3VL2710-2SP36-0AA0



Manufacturer	SIEMENS
MPN / Reference	3VL2710-2SP36-0AA0
Catalog number	27102
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-A59ECC5113
Generated	2026-08-06

Product Overview

circuit breaker VL160H high breaking capacity Icu=70kA, 415V AC 3-pole, motor/generator prot. Electronic Trip Unit ETU10M, LI In=100A, rated current IR=40...100A, overload protection, II=1.25 to 11xIN, short-circuit protection with screw terminals without auxiliary release without auxiliary/alarm switch

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Moulded Case Circuit Breakers 3VL S**

Additional Product Information

ETIM: EC000074 - Motor protection circuit-breaker
Value Unit
With thermal protection (EF006233) -
Type of control element (EF006976) -
Overload release current setting (EF002336) ['40', '100'] A
Adjustment range undelayed short-circuit release (EF007131) ['125', '1100'] A
Phase failure sensitive (EF007400) true
Switch off technique (EF007007) Magnetic
Rated operating voltage (EF001435) ['690', '690'] V
Rated permanent current Iu (EF001389) 100.0 A
Rated operation power at AC-3, 230 V (EF007025) 18.4 kW
Rated operation power at AC-3, 400 V (EF001364) 55.4 kW
Type of electrical connection of main circuit (EF006819) Screw connection

Device construction (EF008240) Built-in device fixed built-in technique

With integrated auxiliary switch (EF001387) false

With integrated under voltage release (EF001390) false

Number of poles (EF001391) 3

Degree of protection (IP) (EF005474) IP20

Height (EF000040) 174.5 mm

Width (EF000008) 104.5 mm

Depth (EF000049) 106.5 mm

Rated short-circuit breaking capacity Icu at 400 V, AC (EF007049) - kA

Product

Article Number (Market Facing Number) 3VL2710-2SP36-0AA0

Product Description circuit breaker VL160H high breaking capacity Icu=70kA, 415V AC 3-pole, motor/generator prot.

Electronic Trip Unit ETU10M, LI In=100A, rated current IR=40...100A, overload protection, II=1.25 to 11xIN, short-circuit protection with screw terminals without auxiliary release without auxiliary/alarm switch

Product family Not available

Product Lifecycle (PLM) PM400:Phase Out Star...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3VL2710-2SP36-0AA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.