

INDUSTRIAL COMPONENT DATA

3VL9400-3MJ00 SIEMENS accessory for VL400, mot. op. mech. w/ strd en. mech 24 VDC

Brand: SIEMENS | Manufacturer Part Number: 3VL9400-3MJ00



Manufacturer	SIEMENS
MPN / Reference	3VL9400-3MJ00
Catalog number	94003
Category	Accessories/spare parts for low-voltage switch technology
Minimum order	1 Pcs
Document ID	EO-4EEDC70C5E
Generated	2026-08-03

Product Overview

accessory for VL400, mot. op. mech. w/ strd en. mech 24 VDC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Moulded Case Circuit Breakers 3VL S
--------------	---

Additional Product Information

ETIM: EC002498 - Accessories/spare parts for low-voltage switch technology

Value Unit

Type of accessory/spare part (EF000215) Other

accessory for VL400, mot. op. mech. w/ strd en. mech 24 VDC

Model

product brand name SENTRON

Product designation Motorized operating mechanism with stored energy mechanism

Design of the product Accessory for VL400

Type of the driving mechanism Motorized operating mechanism with spring energy store

General technical data

Break time / typical 5 s

Pulse duration / minimum 50 ms

Operating frequency / maximum 120 1/h

Voltage

Fuse protection type / for external auxiliary power supply / required NEOZED fuse (gL/gG): 6 A / miniature circuit breaker, C

char.: 6 A

operating range factor control supply voltage rated value

? at DC / initial value 0.85

? at DC / full-scale value 1.1

? at AC / at 50 Hz / initial value 0.85

? at AC / at 50 Hz / full-scale value 1.1

? at AC / at 60 Hz / initial value 0.85

? at AC / at 60 Hz / full-scale value 1.1

Protection class

Protection class IP IP30

Current

Make time / typical 0.1 s

Control current

Operating apparent output 200 V·A

Control supply voltage

? at DC / rated value / minimum 24 V

? at DC / rated value / maximum 24 V

Accessories

Accessories Accessories for VL400

Connections

Wire stripping length 10 mm

connectable conductor cross-section / solid

? minimum 0.75 mm²

? maximum 1.5 mm²

Connectable conductor cross-section / stranded

? minimum 0.75 mm²

? maximum 1.5 mm²

connectable conductor cross-section / finely stran...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3VL9400-3MJ00 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.