

INDUSTRIAL COMPONENT DATA

3VL9800-3ML00 SIEMENS accessory for VL1250, VL1600, motorized operating mechanism 42...48V AC/DC

Brand: SIEMENS | Manufacturer Part Number: 3VL9800-3ML00



Manufacturer	SIEMENS
MPN / Reference	3VL9800-3ML00
Catalog number	98003
Category	Accessories/spare parts for low-voltage switch technology
Minimum order	1 Pcs
Document ID	EO-38F9865138
Generated	2026-08-05

Product Overview

accessory for VL1250, VL1600, motorized operating mechanism 42...48V AC/DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Moulded Case Circuit Breakers 3VL S**

Additional Product Information

ETIM: EC002498 - Accessories/spare parts for low-voltage switch technology

Value Unit

Type of accessory/spare part (EF000215) Other

accessory for VL1250, VL1600, motorized operating mechanism 42...48V AC/DC

Model

product brand name SENTRON

Product designation Motorized operating mechanism

Design of the product Accessories for VL1250; VL1600

Type of the driving mechanism motorized operating mechanism

General technical data

Break time / typical 5 s

Pulse duration / minimum 50 ms

Operating frequency / maximum 30 1/h

Voltage

Fuse protection type / for external auxiliary power supply / required NEOZED fuse (gL/gG): 4 A / miniature circuit breaker, C

char.: 4 A

operating range factor control supply voltage rated value

? at DC / initial value 0.85

? at DC / full-scale value 1.1

? at AC / at 50 Hz / initial value 0.85

? at AC / at 50 Hz / full-scale value 1.1

? at AC / at 60 Hz / initial value 0.85

? at AC / at 60 Hz / full-scale value 1.1

Protection class

Protection class IP IP30

Current

Make time / typical 5 s

Control current

Operating apparent output 250 V·A

Control supply voltage

? at DC / rated value / minimum 48 V

? at DC / rated value / maximum 42 V

? at AC / at 50 Hz / rated value / minimum 42 V

? at AC / at 50 Hz / rated value / maximum 48 V

? at AC / at 60 Hz / rated value / minimum 42 V

? at AC / at 60 Hz / rated value / maximum 48 V

Accessories

Accessories Accessories for VL1250; VL1600

Connections

Wire stripping length 10 mm

connectable conductor cross-section / solid

?...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3VL9800-3ML00 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.