

INDUSTRIAL COMPONENT DATA

3WL1006-1AC13-0AA0 SIEMENS fixed-mounted circuit breakers 4-pole, frame size 0, IEC N conductor on the left ..

Brand: SIEMENS | Manufacturer Part Number: 3WL1006-1AC13-0AA0



Manufacturer	SIEMENS
MPN / Reference	3WL1006-1AC13-0AA0
Catalog number	10000
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-C91F12F368
Generated	2026-08-02

Product Overview

fixed-mounted circuit breakers 4-pole, frame size 0, IEC N conductor on the left In=630A to 690V, 50/60Hz AC Icu=42kA at 415V Icu=42kA at 500V ETU350 electronic trip units LSI rotary coding switch with tripped signaling switch, rtc and 4Aux auxiliary switches protection adjustable I: Ir 0.4-1 In s: isd 1-10 In; l:ii 1-15 In w. var. n conductor protection front maine connections no communication link, no metering funct. Manual operating mechanism of the spring energy store With mechanical closing Without 2nd auxiliary release Without 1st auxiliary release

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > 3WL Air Circuit Breakers

Additional Product Information

ETIM: EC000228 - Power circuit-breaker for trafo/generator/installation protection

Value Unit

Rated voltage (EF003977) - V

Integrated earth fault protection (EF007296) -

Overload release current setting (EF002336) - A

Adjustment range short-term delayed short-circuit release (EF007129) - A

Number of auxiliary contacts as normally open contact (EF001376) -

Number of auxiliary contacts as normally closed contact (EF001377) -

Degree of protection (IP) (EF005474) -

Type of control element (EF006976) -

Rated short-circuit breaking capacity Icu at 400 V, 50 Hz (EF007048) - kA

Complete device with protection unit (EF008906) -
Position of connection for main current circuit (EF006671) -
Number of auxiliary contacts as change-over contact (EF003531) -
Suitable for DIN rail (top hat rail) mounting (EF007250) -
Motor drive integrated (EF006697) -
Motor drive optional (EF007386) -
With under voltage release (EF007518) -
Number of poles (EF001391) -
With switched-off indicator (EF007006) -
Rated permanent current I_n (EF001389) - A
Type of electrical connection of main circuit (EF006819) -
DIN rail (top hat rail) mounting optional (EF008904) -
Adjustment range undelayed short-circuit release (EF007131) - A
Device construction (EF008240) -

Product

Article Number (Market Facing Number) 3WL1006-1AC13-0AA0

Product Description fixed-mounted circuit breakers 4-pole, frame size 0, IEC N conductor on the left $I_n=630A$ to 690V, 50/60Hz AC $I_{cu}=42kA$ at 415V $I_{cu}=42kA$ at 500V ETU350 electronic trip uni...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3WL1006-1AC13-0AA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.