

INDUSTRIAL COMPONENT DATA

3WL1006-1AC32-0AA0 SIEMENS withdrawable circuit breakers with guide frame and PSS 3-pole, frame size 0, IEC ..

Brand: SIEMENS | Manufacturer Part Number: 3WL1006-1AC32-0AA0



Manufacturer	SIEMENS
MPN / Reference	3WL1006-1AC32-0AA0
Catalog number	10000
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-839EA29458
Generated	2026-08-03

Product Overview

withdrawable circuit breakers with guide frame and PSS 3-pole, frame size 0, IEC In=630A to 690V, 50/60Hz AC Icu=42kA at 415V Icu=42kA at 500V ETU350 electronic trip units LSI rotary coding switch with tripped signaling switch, RTC and 4Aux auxiliary switches protection adjustable I: Ir 0.4-1 In s: isd 1-10 In; I:ii 1-15 In w. var. n conductor protection rear horizontal connection no communication link, no metering funct. Manual operating mechanism of the spring energy store With mechanical closing Without 2nd auxiliary release Without 1st auxiliary release

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > 3WL Air Circuit Breakers**

Additional Product Information

ETIM: EC000228 - Power circuit-breaker for trafo/generator/installation protection

Value Unit

Overload release current setting (EF002336) - A

Integrated earth fault protection (EF007296) -

Number of auxiliary contacts as change-over contact (EF003531) -

Type of control element (EF006976) -

Motor drive optional (EF007386) -

Complete device with protection unit (EF008906) -

Number of auxiliary contacts as normally open contact (EF001376) -

Adjustment range short-term delayed short-circuit release (EF007129) - A

With switched-off indicator (EF007006) -

Rated short-circuit breaking capacity Icu at 400 V, 50 Hz (EF007048) - kA

With under voltage release (EF007518) -

Rated voltage (EF003977) - V

Motor drive integrated (EF006697) -

Adjustment range undelayed short-circuit release (EF007131) - A

Device construction (EF008240) -

Number of auxiliary contacts as normally closed contact (EF001377) -

DIN rail (top hat rail) mounting optional (EF008904) -

Rated permanent current Iu (EF001389) - A

Degree of protection (IP) (EF005474) -

Position of connection for main current circuit (EF006671) -

Suitable for DIN rail (top hat rail) mounting (EF007250) -

Type of electrical connection of main circuit (EF006819) -

Number of poles (EF001391) -

Product

Article Number (Market Facing Number) 3WL1006-1AC32-0AA0

Product Description withdrawable circuit breakers with guide frame and PSS 3-pole, frame size 0, IEC In=630A to 690V, 50/60Hz AC Icu=42kA at 415V Icu=42kA at 500V ETU350 electronic trip uni...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3WL1006-1AC32-0AA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.