

INDUSTRIAL COMPONENT DATA

3WL1010-3AC13-0AA0 SIEMENS fixed-mounted circuit breakers 4-pole, frame size 0, IEC N conductor on the left ..

Brand: SIEMENS | Manufacturer Part Number: 3WL1010-3AC13-0AA0



Manufacturer	SIEMENS
MPN / Reference	3WL1010-3AC13-0AA0
Catalog number	10000
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-6AE33741E3
Generated	2026-08-02

Product Overview

fixed-mounted circuit breakers 4-pole, frame size 0, IEC N conductor on the left $I_n=1000A$ to 690V, 50/60Hz AC $I_{cu}=66kA$ at 415V $I_{cu}=50kA$ at 500V $I_{cu}=50kA$ at 690V ETU350 electronic trip units LSI rotary coding switch with tripped signaling switch, RTC and 4Aux auxiliary switches protection adjustable I: I_r 0.4-1 I_n s: i_{sd} 1-10 I_n ; I_{ii} 1-15 I_n w. var. n conductor protection front main connections no communication link, no metering funct. Manual operating mechanism of the spring energy store With mechanical closing Without 2nd auxiliary release Without 1st auxiliary release

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > 3WL Air Circuit Breakers

Additional Product Information

ETIM: EC000228 - Power circuit-breaker for trafo/generator/installation protection

Value Unit

Number of auxiliary contacts as change-over contact (EF003531) -

Device construction (EF008240) -

Motor drive optional (EF007386) -

With under voltage release (EF007518) -

Rated permanent current I_u (EF001389) - A

Overload release current setting (EF002336) - A

Rated voltage (EF003977) - V

Type of control element (EF006976) -

Integrated earth fault protection (EF007296) -

Number of auxiliary contacts as normally open contact (EF001376) -
DIN rail (top hat rail) mounting optional (EF008904) -
Suitable for DIN rail (top hat rail) mounting (EF007250) -
Motor drive integrated (EF006697) -
Rated short-circuit breaking capacity Icu at 400 V, 50 Hz (EF007048) - kA
Complete device with protection unit (EF008906) -
Position of connection for main current circuit (EF006671) -
Number of auxiliary contacts as normally closed contact (EF001377) -
Number of poles (EF001391) -
With switched-off indicator (EF007006) -
Adjustment range short-term delayed short-circuit release (EF007129) - A
Adjustment range undelayed short-circuit release (EF007131) - A
Degree of protection (IP) (EF005474) -
Type of electrical connection of main circuit (EF006819) -

Product

Article Number (Market Facing Number) 3WL1010-3AC13-0AA0

Product Description fixed-mounted circuit breakers 4-pole, frame size 0, IEC N conductor on the left In=1000A to 690V, 50/60Hz AC Icu=66kA at 415V Icu=50kA at 500V Icu=50kA at 690V ETU350 e...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3WL1010-3AC13-0AA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.