

INDUSTRIAL COMPONENT DATA

4NC5328-2CE20 SIEMENS Window-type current transformer, Class 1 750 A/5 A, 5 VA

Brand: SIEMENS | Manufacturer Part Number: 4NC5328-2CE20



Manufacturer	SIEMENS
MPN / Reference	4NC5328-2CE20
Catalog number	53282
Category	Current transformer
Minimum order	1 Pcs
Document ID	EO-E96441967B
Generated	2026-08-02

Product Overview

Window-type current transformer, Class 1 750 A/5 A, 5 VA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > SITOR Extra-fast Fuses

Additional Product Information

ETIM: EC002048 - Current transformer

Value Unit

Model (EF000010) Other

Primary rated current (EF007405) 750 A

Secondary rated current (EF007471) 5 A

Secondary rated apparent power (EF007470) 5.0 VA

Accuracy class (EF001532) class 1

Over current limiting factor (EF007511) FS 10

Calibrated (EF003706) -

With shock protection (EF008186) true

Opening diameter (EF005153) 36.0 mm

Snap mounting (EF007462) -

With copper rail (EF007380) -

Secondary connection (EF007469) Screw connection

Number of primary inputs (EF006947) 1

Height opening (EF004778) - mm

Width opening (EF004565) - mm

Window-type current transformer, Class 1 750 A/5 A, 5 VA

Model

product brand name SENTRON

Product designation Window-type current transformers

Operating apparent output / rated value 5 V·A

Reference code / acc. to DIN 40719 extended according to IEC 204-2 / acc. to IEC 750 T

Protection class

Protection class IP IP20

? Ratio of input current/output current 750/5 A

? Current / at output / rated value 5 A

? Current / at input / rated value 750 A

Accuracy class / of the current transformer class 1

Product feature / Touch protection Yes

Connections

Type of electrical connection / at output screw-type terminals

Mechanical Design

Height 98 mm

Width 82.5 mm

? Width / of the push-through bus bar / at 1 bus bar / maximum 50 mm

? Width / of the push-through bus bar / in case of 2 bus bars / maximum 40 mm

Depth 80 mm

Mounting type screw fixing

Outer diameter / of the push-through conductor / maximum 36 mm

Environment...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 4NC5328-2CE20 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.