

**INDUSTRIAL COMPONENT DATA**

# 5SE1310 SIEMENS NEOZED fuse-link, D01, 10 A, gR, Un AC: 400 V, Un DC: 250 V, SILIZED

Brand: SIEMENS | Manufacturer Part Number: 5SE1310



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | SIEMENS             |
| MPN / Reference | 5SE1310             |
| Catalog number  | 10000               |
| Category        | D0-system fuse link |
| Minimum order   | 10 Pcs              |
| Document ID     | EO-81014B6E6A       |
| Generated       | 2026-08-01          |

## Product Overview

NEOZED fuse-link, D01, 10 A, gR, Un AC: 400 V, Un DC: 250 V, SILIZED

NEOZED-SILIZED fuse cartridge, p/semiconductor protection, 400V AC/250V DC, gR, size D01, 10A ( \*\* ATTENTION : Price per 1 Unit and Minimum Quantity / Order Multiple 10 Units \*\* ). Cancelations and returns limited. Consult conditions.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path

SIEMENS &gt; POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR &gt; Fuses Neozed, Diazed, Silized, Minized

## Additional Product Information

Technical data

NEOZED fuse-link, D01, 10 A, gR, Un AC: 400 V, Un DC: 250 V, SILIZED

Model

product brand name SENTRON

product designation NEOZED fuse link

design of the product SILIZED

General technical data

size of fuse system / according to EN 60269-1 D01

operating class of the fuse link gR

Supply voltage

supply voltage

? at DC 250 V

operating voltage / rated value 400 V

**Dissipation**

power loss [W] / for rated value of the current / at AC / in hot operating state / per pole 6.9 W

**Main circuit**

operational current / rated value 10 A

**Appearance**

color coding of the fuse link Red

breaking capacity maximum short-circuit current (Icu) / at AC / rated value 50 kA

**Mechanical Design**

net weight 7 g

ambient temperature / during operation

? minimum 40 °C

? maximum 40 °C

**Downloads and manuals**

General Product Approval Declaration of Conformity other

**Confirmation****Environmental Confirmations****Miscellaneous****Further information**

Information- and Downloadcenter (Catalogs, Brochures,...) <http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system) <https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SE1310>

Service&Support (Manuals, Certificates, Characteristics,

FAQs,...) <https://support.industry.siemens.com/cs/ww/en/ps/5SE1310>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams,

...) [http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5SE1310](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SE1310)

CAX-Online-Generator <http://www.siemens.com/cax>

Tender specifications <http://www.siem...>

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send SIEMENS / 5SE1310 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](http://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.