

INDUSTRIAL COMPONENT DATA

5SE1325 SIEMENS NEOZED fuse-link, D02, 25 A, gR, Un AC: 400 V, Un DC: 250 V, SILIZED

Brand: SIEMENS | Manufacturer Part Number: 5SE1325



Manufacturer	SIEMENS
MPN / Reference	5SE1325
Catalog number	10000
Category	D0-system fuse link
Minimum order	10 Pcs
Document ID	EO-C2678BDD3D
Generated	2026-08-03

Product Overview

NEOZED fuse-link, D02, 25 A, gR, Un AC: 400 V, Un DC: 250 V, SILIZED

NEOZED-SILIZED fuse cartridge, p/semiconductor protection, 400V AC/250V DC, gR, size D02, 25A (** ATTENTION : Price per 1 Unit and Minimum Quantity / Order Multiple 10 Units **). Cancelations and returns limited. Consult conditions.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Fuses Neozed, Diazed, Silized, Minized

Additional Product Information

Technical data

NEOZED fuse-link, D02, 25 A, gR, Un AC: 400 V, Un DC: 250 V, SILIZED

Model

product brand name SENTRON

product designation NEOZED fuse link

design of the product SILIZED

General technical data

size of fuse system / according to EN 60269-1 D02

operating class of the fuse link gR

Supply voltage

supply voltage

? at DC 250 V

operating voltage / rated value 400 V

Dissipation

power loss [W] / for rated value of the current / at AC / in hot operating state / per pole 8.2 W

Main circuit

operational current / rated value 25 A

Appearance

color coding of the fuse link Yellow

breaking capacity maximum short-circuit current (Icu) / at AC / rated value 50 kA

Mechanical Design

net weight 13 g

ambient temperature / during operation

? minimum 40 °C

? maximum 40 °C

Downloads and manuals

General Product Approval Declaration of Conformity other

Confirmation**Miscellaneous****Environmental Confirmations****Further information**

Information- and Downloadcenter (Catalogs, Brochures,...) <http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system) <https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SE1325>

Service&Support (Manuals, Certificates, Characteristics,

FAQs,...) <https://support.industry.siemens.com/cs/ww/en/ps/5SE1325>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams,

...) http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SE1325

CAX-Online-Generator <http://www.siemens.com/cax>

Tender specifications <http://www....>

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 5SE1325 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.